

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 36; & 1 T25-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 7 Page 3029)

Set 1/4 sec. post from which
A W.Oak, 10" dia., bears S.58°W., 37 lks.
A pine, 15" dia., bears N.20°W., 22 lks.

Douglas Co. Surveyors Office - Milo Godfrey - May 1963 - C.S.
File 53/9-16

No trace found.

Kris DeGroot - For: Douglas Co. Inc - 8/8/2008 - 2008-0061A-G

Set - 5/8"x30" iron rod w/2" Alum. cap, 27" in the ground
stamped:

T24S
1/4 S 36 R
S 1 4
T25S W
2008
PLS 1941

New - A 7" cedar bears S.71°45'W., 21.7 ft scribed "1/4 S1 BT"
A 6" cedar bears N.33°45'W., 16.3 ft. scribed "1/4 S1 BT"
5/8"x30" IR w/plastic cap bears N.71°49'56"E., 35.0 ft.
5/8"x30" IR w/plastic cap bears S.33°52'07"E., 40.0 ft.

Note- All new BTs have double blazed faces w/a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown & distances are measured to a nail in the root crown at the side & center of the tree w/a total station. All BTs have a 6" red band painted around the tree & the blazed face painted red & BT signs nailed to the tree. All new 5/8"x30" iron rod reference monuments have a plastic cap stamped "BTS ENG-SURV"