

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 640140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Kris DeGroot - For: Douglas Co. Inc - 8/8/2008 - 2008-0061A-G

-----  
Set - 5/8"x30" iron rod w/2" Alum. cap, 28" in the ground stamped:

T24S  
C ¼  
S 36

●  
2008

PLS 1941

New - A 10" Cedar bears N.11°W., 29.8 ft. scribed "C¼ S36 BT"  
A 21" D.Fir bears S.50°W., 28.2 ft. scribed "C¼ S36 BT"  
5/8"x30" IR w/plastic cap bears N.50°00'23"E., 25.0 ft.  
5/8"x30" IR w/plastic cap bears S.0°02'41"W., 50.0 ft.

Note- All new BTs have double blazed faces w/a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown & distances are measured to a nail in the root crown at the side & center of the tree w/a total station. All BTs have a 6" red band painted around the tree & the blazed face painted red & BT signs nailed to the tree. All new 5/8"x30" iron rod reference monuments have a plastic cap stamped "BTS ENG-SURV"