

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 25

Alias	Description

BLM Resurvey by C. Albert White & Norman J. McDonald, Cadastral Surveyors, under Group #'s 243, 350, & 513, surveyed April/July 1963 - (DCSO records Vol. 32 Page(s) 13468)

Point for the center ¼ sec. cor. of sec. 25, at intersection with E & W center line.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd: C ¼ S25
1963

from which

A Fir, 32" dia., bears N.41¼°W., 48 lks., mkd: C¼ S25 BT.

A Fir, 12" dia., bears S.7°E., 104 lks., mkd: C¼ S25 BT.

FD. ok by Kris DeGroot, 8/2008 - 2008-0061A-G

Douglas Co. Surveyor's Office - Crew: Stephen Flause & Mike Koch - 4/13/2016 - C.S. File 67/44-6

Found - 2½" dia. Iron post by C. A. White & N. J. McDonald, USBLM Cadastral Surveyors in 1963 per USBLM plat No. 5279, firmly set, projecting 4" above the ground with a 3¼" dia. Brass cap (properly) mkd. BTs by C.A. White and N.J. McDonald in 1963 -

12" dia. Very rotted fir stump bears S.7°E., 67.1 ft. with no blaze evidence remaining (rec. 104 lks.)

A 28" dia. x 5 ft. tall metal capped fir stump with no bark remaining bears N.41¼°W., 31.7 ft. with scribe marks "C ¼ S25 BT" visible on a partially healed blaze.

New BTs- A 14" dia. D.Fir bears N.72½°E., 17.5 ft. scribed "C¼ S25 CS BT"

A 11" dia. D.Fir bears S.62½°E., 25.7 ft. scribed "C¼ S25 CS BT"

A 17" dia. D.Fir bears S.72½°W., 20.6 ft. scribed "C¼ S25 CS BT"

Compass declination - 15°E

Location & comments - All BTs have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown unless otherwise noted. Corner falls on a moderate south slope in an old fir reprod. Unit approximately 280 ft. South of a sharp curve in a forest access road.

