TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Oscar F. Theil, Contract #658 dated May 1896 (DCSO records Vol. 7 Page(s) 3057)

Set a Cedar post 3’ long, 3" sq. 24" in the ground for ¼ sec. cor. mkd. ¼ S on N face from which
A Cedar, 5" dia, bears N.45°W., 8 lks., mkd: ¼ S BT
A Fir, 12" dia., bears S.41½°W., 8 lks., mkd: ¼ S BT
This corner stands 40 ft. above the branch; keep on ascending.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - June 1963 - C.S. File 53/9-102

Found - Cedar N.45°W., 5.3’, uprooted, down & badly rotted, previously opened, scribing vis., portion of "S" & "B".
No trace remains of SW BT.
Set - Brass cap at cor. mkd: County Surveyor’s Office, 1963 T24S R4W ¼ S24/S25
New BTs- 12" Hemlock N.23°E., 9.6’ mkd: ¼ S24 CS BT.
12" Red Cedar S.17°W., 27.4’ mkd: ¼ S25 CS BT.
Corner lies on fairly steep East slope, approx. 65’ West of small stream.

Found & used - BLM Resurvey by C. Albert White & Norman J. McDonald, Cadastral Surveyors, under Group #’s 243, 350, & 513, surveyed April/July 1963 - (DCSO records Vol. 32 Page(s) 13466-67)

Fd. Ok by D. Edwards 3/2007 - CS File 65/61-3