

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Oscar F. Theil, Contract #658, May 1896 (DCSO records Vol. 7 Page(s) 3059)

Set a Fir post, 3' long 3" sq. 24" in the ground for the ¼ sec. cor. mkd: ¼ S on N face from which
A Fir, 36" dia., bears S.85½°W., 20 lks., mkd: ¼ S BT
A Fir, 10" dia, bears N.23½°W., 40 lks., mkd: ¼ S BT

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - March 1963 - C.S. File 53/9-38

Found - 28" D.Fir, N.23½°W., 26.4', has been opened previously, good scribing.
36" Fir, old uproot, dead, S.85½°W., 13.2', face down, no scribing vis.
Set - Brass cap at cor. mkd: County Surveyor's Office
T24S R4W ¼ S13/S24 1963
New BT - 54" D.Fir, S.46°W., 66.5', mkd: ¼ S24 CS BT.
Rescribe -
28" D.Fir, N.23½°W., 26.4', mkd: ¼ S13 CS BT.
Cor. lies approx. 35' SE of old logging rd running NE & SE.