

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION CC for Secs. 24 & 25 only (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCS0 records Vol. 7 Page(s) 3056-57)

-----  
At intersection Set a sandstone 12x8x6 ins., 8" in the ground for closing cor. of secs. 24 & 25 marked CC on W. with 2 grooves on S. and 4 grooves on N. faces, from which

A Hemlock 16" dia., bears N.65°W., 29 lks. dist. mkd. T24S R4W S24 BT.

A Hemlock 8" dia., bears S.61°W., 54 lks. dist. mkd. T24S R4W S25 BT.

The marks on the old post and bearing trees referring to the new work were effaced or corrected.

B.B. Irving, Surveyor - Richardson, Farrell, witnesses - Dec. 17, 1948 - C.S. File 43/12 & C.S. 44/47-1

-----  
Trees as recorded in the government notes. 12" Hemlock and 30" Hemlock. Blazes chopped out, marked T24S R4W BT. Found unmarked rock proper dimensions, reset at proper location.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCS0 records Vol. 27 Page(s) 11463-64)

-----  
The closing cor. of secs. 24 and 25, monumented with a sandstone 13 x 10 x 6 ins., firmly set, mkd. with 4 grooves on N., 2 grooves on S., and CC on W. face; from which the original bearing trees:

A Hemlock 24" dia., bears N.57°45'W., 31 lks. dist., with the scribe marks T24S R4W S2 visible on previously opened old blaze. (Rec. N.65°W., 29 lks. dist.)

A Hemlock 12" dia., bears S.62°W., 52½ lks. dist. with the scribe marks T24S R4W S25 BT visible on previously opened old blaze. (Rec. S.61°W., 54 lks. dist.)

At the corner point

Set an iron post 3 ft. long, 2" dia., 28" in the ground with the original stone deposited at the base, with brass cap mkd.

CC	T 24 S S 24 S 25 R 4 W	T 24 S R 3 W S 30
	1950	

from which

A Fir 14" dia., bears N.38¼°W., 88 lks. dist. mkd. T24S R4W S24 CC BT.

A Cedar 16" dia., bears S.71½°W., 112 lks. dist. mkd. T24S R4W S25 CC BT.

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION C C for Secs. 24 & 25 only (East)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

M. Godfrey reports the 14" Fir gone. - June 13, 1963 CS 53/9-101(B)

David Edwards - For: Seneca Jones Timber Co. - March 2014 - C.S. File 65/81-10

-----  
Found - BLM brass cap.  
          48" Hemlock N.57¾°W., 20.5'  
          17" hemlock (unrec'd) S.77°W., 7.2' } healed blaze  
Set - 6 ft. steel post 2' south