

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION C C for Secs. 13 & 24 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3058)

At point of intersection, I set a Hemlock post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 13 and 24, marked CC T24S R4W on W.; S13 on N.; and S24 on S. faces with 3 grooves on S. and N. faces, from which

A Fir 24" dia., bears N.29½°W., 9 lks. dist. mkd. T24S R4W S13 BT.

A Fir 24" dia., bears S.14°W., 11 lks. dist. mkd. T24S R4W S24 BT.

All marks on old post and witness trees referring to the new work were effaced or corrected.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11466)

The closing cor. of secs. 13 and 24, T24S R4W determined at the record bearing and distance from each of the original bearing trees as follows:

A Fir 30" dia., dead and down, bears N.29½°W., 9 lks. dist. with surface scar indicating old blaze.

A Fir 30" dia., dead and down, bears S.14°W., 11 lks. dist., with the scribe marks S 24 BT uncovered.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 24 S	T 24 S
S 13	R 3 W
S 24	S 13
R 4 W	
1950	

from which

A Fir 13" dia., bears N.73°W., 69 lks. dist. mkd. T24S R4W S13 CC BT.

A Fir 15" dia., bears S.75½°W., 88 lks. dist. mkd. T24S R4W S24 CC BT.

Fd. OK, Oct. 9, 1985 by R. Geisler - C.S. File 63/22-13