

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11467)

Point for the ¼ sec. cor. of sec. 13, T24S R4W., at midpoint of the E. bdy. of sec. 13.
Set an iron post 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd. ¼ S 13 |
1950

from which
A Fir 12" dia., bears N.67°W., 92 lks. dist. mkd. ¼ S13 BT
A Fir 22" dia., bears S.30°W., 31 lks. dist. mkd. ¼ S13 BT

Fd. OK, Oct. 9, 1985 by R. Geisler - C.S. File 63/22-12

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed May 2002-May 2003, - (DCSO records Vol. 54 Page(s) 21112-3)

The 1/4 sec. cor. of sec. 13 only, T24S R4W., on the E bdy of the Tp, monumented with an iron post, 1" dia., firmly set, buried 1" below the ground, with brass cap (properly) mkd., from which the remains of BTs mkd. by Price
A sawed fir stump, 27" dia., bears N.67°W., 60.7 ft., with a healed double blaze.
A fir, 41" dia., bears S.30°W., 20.5 ft., with a healed blaze.

and a new BT
A fir, 7" dia., bears N.78¾°W., 27.0 ft., mkd. ¼ S13 BT.
Corner is located 80.0 ft. South of a graveled road, 12 ft. wide, bears N.85°W. and S.85°E, and 3.0 ft. East of a woven wire fence, extending North and South.

The geographic position (NAD 1983 (CORS)) of this cor. as determined by NAVSTAR GPS, utilizing dual frequency, carrier phase GPS receivers. (Trimble 5700), relative to the National Spatial Reference System, is as follows:
Latitude: 43°28'58.86"N., Longitude: 123°06'30.30"W.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2656, surveyed Sept./Nov. 2012 - (DCSO records Vol. 58 Page(s) 23003)

The ¼ sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with an iron post, 1" dia., firmly set, buried 2" below ground, with brass cap (properly) mkd.

continued next page

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of bearing trees mkd. by Price in 1950
A fir, 42" dia., bears S.30°W., 20.5 ft., with a healed
blaze.

A sawed fir stump, 27" dia., bears N.67°W., 60.7 ft.
with a healed blaze.

and a bearing tree mkd. by Moore and Browning in 2002-03

A fir, 11" dia., bears N.78¾°W., 27.0 ft., with a healed
blaze.

Corner is located 3 ft. W. of a fence extending N. and S.,
and 80 ft. S. of a gravel road, bears N.88°E. and S.80°W.