

PRIMARY CORNER DESCRIPTION C C for Secs. 12 & 13 only, (East)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3060)

 At the point of intersection, I set a Fir post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 12 & 13, mkd. C C T24S R4W on W.; S12 on N.; and S13 on S. faces, with 2 grooves on N. and 4 grooves on S. faces, from which
 A Cedar 12" dia., bears S.73°W., 33 lks. dist. mkd. T24S R4W S13 BT.
 A Fir 8" dia., bears N.5°W., 47 lks. dist. mkd. T24S R4W S12 BT.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11468)

 Point for the closing cor. of secs. 12 and 13, T24S R4W on the W. bdy. of sec. 7.
 Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap mkd.

C C	T 24 S S 12 S 13 R 4 W	T 24 S R 3 W S 7
	1950	

from which
 A Fir 20" dia., bears N.54°W., 73 lks. dist. mkd. T24S R4W S12 CC BT.
 A Fir 8" dia., bears S.81½°W., 47 lks. dist. mkd. T24S R4W S13 CC BT.

(AMENDED CORNER)
 From this corner, Thiel's original closing cor. of secs. 12 and 13 bears East, 62 lks. dist., determined at the record distance from each of the original bearing trees which stand as follows:

 A Fir 20" dia., bears N.6°W., 47 lks. dist., with the scribe marks BT visible in the partially opened old blaze. (Rec. brg. N.5°W.) I add the marks AM on this old bearing tree.
 A Cedar 24" dia., bears S.72°W., 33 lks. dist., with the scribe marks BT visible in the partially opened old blaze. (Rec. brg. S.73°W.) I add the marks AM on this old bearing tree.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 12 & 13 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - June 12, 1963 - C.S. File 53/9-90& 106

Found - GLO brass cap set in 1950 mkd. as described in the govt. notes.

8" Fir S.81½°W., 31.0 ft. is broken, down and dead, some scribing visible on partly rotted face.

No trace of NW. bearing tree.

New BTs- 11" Red Cedar N.42°W., 78.7 ft. mkd. T24S R4W CC S12 CS BT.

9" Red Cedar S.46°W., 14.9 ft. mkd. T24S R4W CC S13 CS BT.

(AMENDED CORNER)

Found - 34" Cedar S.73°W., 21.8 ft. previously opened, old scribing "13 BT" visible on old face. Tree still alive, but top broken out approx. 40 ft. above ground, newer scribing visible "AM BT"

32" Fir N.6°W., 31.0 ft. has been opened previously but scar nearly healed shut. No scribing visible, newer blaze below, also healed over.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 4 W

Orig. CC S12 |

S13 |

1963

From this corner, brass cap set by Price for CC S12 & S13, bears West 41.6 ft. (63 lks. instead of 62 lks.)

Did Not Mark any New Bearing Trees.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2656, surveyed Sept./Nov. 2012 - (DCSO records Vol. 58 Page(s) 23004-5)

The closing cor. of secs. 12 and 13, on the E. bdy. of the Tp., perpetuated by Godfrey, in 1963, monumented with an iron post, 2" dia., firmly set, projecting 13" above ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Godfrey

A cedar, 24" dia., bears S.45¼°W., 14.8 ft., with a healed double blaze.

A cedar, 23" dia., bears N.42¼°W., 78.6 ft., with a healed double blaze.

Corner is located 3 ft. E. of the cor. of fences extending N, S, and W.

From this cor., the original closing cor., perpetuated by Godfrey, bears S.89°32'44"E., 41.2 ft., monumented with an iron post, 1¼" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd. continued next page

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION C C for Secs. 12 & 13 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the original bearing trees

A cedar, 38" dia., bears S.72°W., 21.8 ft., with no marks visible on an open blaze and with scribe marks AM visible alongside.

A fir, 38" dia. bears N.6°W., 31.0 ft. with a healed blaze