

PRIMARY CORNER DESCRIPTION C C for Secs. 1 and 12 only, (East)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3062)

 At point of intersection, I set a Cedar post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 12 and 1, mkd. CC T24S R4W on W.; S1 on N. and S12 on S. faces, with one groove on N. and 5 grooves on S. faces, from which
 A Fir 36" dia., bears N.8½°W., 55 lks. dist. mkd. T24S R4W S1 BT.
 No other tree within limits; dug a pit 24x18x12 ins., S. 3 ft. and W. of post 7 ft. dist., and raised mound of earth 4 ft. base, 2 ft. high W. of cor.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11470)

 Point for the closing cor., at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

	T 24 S		T 24 S
	S 1		R 3 W
C C	-----		S 6
	S 12		
	R 4 W		
			1950

from which
 A Fir 28" dia., bears N.31½°W., 38 lks. dist. mkd. T24S R4W S1 CC BT.
 A Fir 26" dia., bears S.54°45'W., 49 lks. dist. mkd. T24S R4W S12 CC BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - Feb/Mar. 1963 - C.S. File 53/9-4

 Found - GLO brass cap dated 1950.
 28" Fir N.31½°W., 25.1 ft., recent blowdown, portions of scribe marks visible in not completely healed scar.
 26" Fir S.54°45'W., 32.3 ft., recent blowdown, scar visible., lying face down.
 New BTs- 13" D.Fir N.57°W., 10.2 ft. mkd. T24S R4W S1 CC CS BT.
 7" I.Cedar S.79°W., 28.2 ft. mkd. CC S12 CS BT.
 (13" D.Fir, tree down June 1963. Marked New BT:)
 7" Hemlock N.57°W., 70.8 ft. scribed CC S1 CS BT.

continued next page

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION C C for Secs. 1 and 12 only, (East)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Les Roberts - For: Seneca Jones Timber Co. - Oct. 1999 - M133-54

Found - 1950 GLO iron pipe & brass cap.
28" Fir stump, N.31°W., 25.1' (scribe vis.) 1950 BT.
14" Cedar, S.79°W., 28.2' (scar vis.) 1963 BT.
Set - 5" Fir N.42°E., 19.2' (scribed/metal washer/painted red)
5" Fir S.40°E., 34.1' (scribed/metal washer/painted red)