

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2968-69)

-----  
Set Chinquapin post 3 ft. long, 3" sq., 24" in the ground for ¼ sec.cor. mkd. ¼ S on the W. face, from which  
A Fir 10" dia., bears N.70°E., 33 lks. dist. mkd. ¼ S BT.  
A Cedar 16" dia., bears S.35°W., 46 lks. dist. mkd. ¼ S BT.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3078)

-----  
I made a diligent search for the ¼ sec. cor. but failed to find any traces of the same or the bearing trees belonging to it.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11471)

-----  
Point for the ¼ sec. cor. of sec. 1, T24S R4W, at proportionate distance.  
Set an iron post 3 ft. long, 1" dia., 28" in the ground with brass cap mkd. ¼ S 1 |  
1950  
from which  
A Fir 20" dia., bears N.44°W., 73 lks. dist. mkd. ¼ S1 BT  
A Fir 14" dia., bears S.54°45'W., 73 lks. dist. mkd. ¼ S1 BT. (Per M. Godfrey, this dist. should be 10.7 ft., not 73 lks. - July 11, 1963)

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed May 2002/May 2003, - (DCSO records Vol. 54 Page(s) 21114-5)

-----  
The ¼ sec. cor. of sec. 1 only, T24S R4W on the E. bdy. of the Tp., monumented with an iron post, 1" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd., from which the remains of bearing trees mkd. by Price  
A sawed fir stump, 18" dia., bears S.54¾°W., 10.7 ft., with a healed blaze. (Record, 48.2 ft.)  
A sawed and decayed fir stump, 38" dia., bears N. 44°W., 48.2 ft., with fragmentary scribe marks visible on a decayed blaze.  
and new bearing trees  
A fir, 9" dia., bears N.81¾°W., 6.1 ft., mkd. ¼ S1 BT.  
continued next page

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 7" dia., bears N.30 $\frac{3}{4}$ °W., 23.9 ft., mkd.  $\frac{1}{4}$  S1 BT.  
Each new bearing tree has a 2 $\frac{1}{2}$ "x  $\frac{1}{4}$ " magnetic nail (Mag Nail)  
driven at the base right side-center.  
The geographic position (NAD 1983 (CORS)) of this cor. as  
determined by NAVSTAR GPS, utilizing dual frequency, carrier  
phase GPS receivers. (Trimble 5700), relative to the National  
Spatial Reference System, is as follows:  
Latitude: 43°30'42.29"N. Longitude: 123°06'26.34"W.