

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T24-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original -Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 7 Page(s) 3084)

Set post cor. to secs. 25, 30, 31, and 36, from which
A W.Oak 30" dia., bears N.35°E., 31 lks.
A W.Oak 40" dia., bears S.64°E., 64 lks.
A Y.Oak 7" dia., bears N.30°W., 74 lks.
A Y.Oak 16" dia., bears South, 81 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, S.A. Bilow - May 14, 1959 - C.S. File 49/124-12

Found - Orig. 16" now 26" B.Oak, South 53.5 ft., I open and find good scribing "S3"
Orig. 7" now 20" B.Oak N.30°W., 48.8 ft., shows good scar. I do not open.
Orig. 40" now 50" W.Oak S.64°E., 42.2 ft., shows good scar. I do not open.
Orig. 30" now 36" W.Oak snag, shows scar, N.35°E., 20.5 ft.

Corner is N.65°W., 6.0 ft. from fence corner, fences running South and East.

Set Brass cap at corner mkd: County Surveyors Office

	S 25	S 30	T24S
R6W	S 36	S 31	R5W
	1959		

New BTs -20" R.Fir bears S.65°W., 37.0 ft. scribed S36 T24S R6W CS BT.

Rescribe now 20" B.Oak N.28½°W., 51.0 ft. scribed S25 T24S R6W CS BT.

20" W.Oak N.2°W., 53.8 ft. scribed S25 T24S R6W CS BT.

10" W.Oak S.31°E., 9.0 ft. scribed S31 T24S R5W CS BT.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - May 22, 1997 - C.S. 64/75-1

Mon. Fd.-2½" dia. Brass cap on a 1½" O.D. iron pipe, protrudes 10" above ground.

Accessories Fd.-

16" now 26" dia. 4' high B.Oak stump, with a previously opened blaze scribing visible "TS", bears south 53.5' (agrees with rec.) OBT

40" now 36" dia. rotted to ground oak stump agrees with rec. "S64°E., 42.2'" OBT.

No other OBT's found

(Cont. Next Page)

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T24-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

20" now 24" dia. 3' high D.Fir stump, with scribing found "BT", bears S.65°W., 37' to root crown (agrees with rec.) 1959.
20" W.Oak now root hole, bears N.2°W. 53.8' (agrees with rec.) 1959.
10" now 10" dia. W.Oak, with a fully healed blaze, bears S.31°E., 9' (agrees with rec.) 1959
New Accessories -
5/8" I.R. protrudes 5" above ground, bears S.48°E., 7.4'.
7" dia. W.Oak, double blazed and scribed "T24S R6W S36 CS BT", bears S.60½°W., 16.2'.
9" dia. W.Oak, double blazed and scribed "T24S R6W S25 CS BT", bears N.15°W., 39.1'.
Corner bears N.35°W. 6' from fence corner running E-W-S