

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; and S. 13, T24-6

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original -Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 7 Page(s) 3082)

-----  
Set ¼ sec. post, from which  
A W.Oak 8" dia., bears S.5°W., 539 lks.  
Made trench, no other tree near.

BLM resurvey by D. Berry and C. Akin, Cadastral Surveyors under Group #'s 826 and 856; and G. Baughman, under Contract #52500-CT5-1116 - surveyed Sept. 1973/Aug. 1975 (DCSO records Vol. 37 Page(s) 15232)

-----  
Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 24 S  
R 6 W R 5 W  
1/4  
S 13 S 18  
1973

from which

A W.Oak 20" dia., bears N.52°E., 21 lks. mkd. ¼ S18 BT  
A W.Oak 16" dia., bears N.58½°W., 29½ lks. mkd. ¼ S13 BT

Fd. OK - Don Bentz - Mar. 1996 - M 125-16