

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3121)

Set post, cor. to secs. 7, 8, 17 and 18, from which
A Y.Oak 18" dia., bears S.4°W., 114 lks.
A Y.Oak 12" dia., bears S.78½°E., 84 lks.
A Y.Oak 8" dia., bears N.70½°E., 68 lks.
A Y.Oak 16" dia., bears N.53°W., 118 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - For: L. Churchill - April 1, 1958 - C.S. File 49/72

Found - Orig. 12" now 22" B.Oak BT, S.78½°E. We find bearing should be S.88½°E., and record dist. 55.4 ft. This BT alive and in good condition. I open and find good scribing "S"

Orig. NE and orig. NW BTs. Both now down and partly rotted. I find good scribing on each BT.

Also find 1" rod at corner.

Set Brass cap alongside 1" I.Rod mkd: County Surveyors Office

T	24	S	R	5	W	
		S	7		S	8
		S	18		S	17
						1958

New BTs -20" R.Fir bears S.33°W., 12.0 ft. scribed S18 T24S R5W CS BT.

10" W.Oak bears N.17½°E., 19.0 ft. scribed S8 T24S R5W CS BT.

6" Laurel bears N.80°W., 13.2 ft. scribed S7 T24S R5W CS BT.

6" W.Oak bears East, 13.2 ft. scribed S17 T24S R5W CS BT.

Corner on N-S fence line.

Fd. OK - Don Bentz - Mar. 1996 - M 125-16

Fd. Ok by Neil Hibbs, June 2005 - M146-21

Fd. Ok by Neil Hibbs, 8/2021 - M178-37