TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 5 & 32 of T25-5

Alias Description
Alias Description
Alias Description
Alias Description

Original - Robert Elder, Contract #31 dated April, 1853 (DCSO Records, Vol. 7 Page 3088)

Set ¼ Sec. post, from which
A W.Oak 20" dia. bears N.39½°W., 60 lks.
A W.Oak 16" dia. bears S.27°W., 37 lks.

Doug. Co. Surveyors Office - Gary Langlitz; Clell Goodwin Vic Cangie; Lenora Ladig - July 31, 1975 - C.S. File 57/34-8

Corner location determined by single proportionate measurement
At the corner point, we set a 1" x 24" I.Pipe with brass cap attached mkd:

DOUGLAS CO. SURVEYOR ¼ S 32 R
1975 S 5 5
W

T 24 S
T 25 S

and set a witness post near the corner. We mark the following bearing tree:
A 6" W.Oak bears N.22°E., 82.6 ft. scribed "¼ S32 CS BT" on a double blaze.
A 5/8" I. Rod set in the west R/W of Interstate Hwy 5 at Engineer's station WL² 1615+79.69 PT=
Llg17+94.46 POT bears S22°W., 101.3 ft.
This corner is located between the West R/W fence and the southbound lanes of Interstate 5. Compass Dec. 20° East.

Fd. ok by Herm Pieske, 10/1998 M 130-55.