

PRIMARY CORNER DESCRIPTION Sec. Cor. 32 & 33; 4 & 5 T25-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder, Contract #31 dated April, 1853 (DCSO Records, Vol. 7 Page 3087)

Set Wit. Post to Cor. of Secs. 4, 5, 32 and 33 which falls in creek (Wit. Post 52 lks. South of true cor.) from which
 A Maple 14" dia. bears S.37½°W., 29 lks.
 An Ash 12" dia. bears S.25°E., 33 lks.

Douglas Co. Surveyors Office - Gary Langlitz & Crew
August 4, 1975 - C.S. File 57/34-10

Corner location determined by single proportionate measurement.
 At the corner point, we set a 1" x 24" I.Pipe flush in the ground, with brass cap attached, marked:

DOUGLAS CO. SURVEYOR	T 24 S	
1975	S 32 S 33	R
	S 5 S 4	5
	T 25 S	W

and marked the following bearing tree and bearing objects:
 A 24" Cottonwood bears S.15°E., 17.6 ft. scribed "T25S R5W S 4 CS BT" on a double blaze.
 An "X" chiseled in the top of the west end of a concrete piling foundation of the 2nd piling North of Cabin Creek along the Southern Pacific Railroad tracks, bears N.81°E., 34.4 ft.
 An "X" chiseled on the top of the West end of a concrete piling support foundation for the 5th piling North of Cabin Creek along the SPRR, bears N.8°E., 39.0'.
 This corner lies approx. 50 ft. North of Cabin Creek and 40 ft. West of the S.P. Railroad tracks. Compass Dec. 20° East.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flaue
- Oct. 14, 1997 - C.S. 64/78-14

Mon. Fd.- 2" dia. brass cap on a iron pipe is found 7" below ground. 1975

Accessories Fd. -
 24" now 22" dia. 7' tall cottonwood snag, with an open rotted single blaze, no scribing visible, bears S.15°E., 17.6' (agrees with rec.) 1975

"X" chiseled in west end of concrete piling, bears N.8°E., 39' (agrees with rec.)

"X" chiseled in west end of concrete piling, bears N.81°E., 34.4' (agrees with rec.) 1975.

(Cont. next page)

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. 32 & 33; 4 & 5 T25-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories -
11" Ash, double blazed and scribed "T25S R5W S4
CS BT, bears S.10°E., 23.3'.
No other trees available
Metal witness post and sign are set 2' north of BC/IP.

Found OK by D. Edwards, July 2000 - 2000-0053
Fd. Ok by M. Schultz, June 2009 - M159-55
Fd. By A Ausland 11/2020 - ST HWY 99-006 C