

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3111)

-----  
Set ¼ sec. post, from which  
A Y.Oak 40" dia., bears N.50°W., 57 lks.  
A W.Oak 16" dia., bears N.54°E., 53 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - March 1960 - C.S. File 49/124-34

-----  
Found - Orig. 16" now 36" W.Oak N.54°E., 35.4 ft. I open and find good scribing "T"  
Orig. NE BT, down and mostly rotted.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 5 W  
¼ S29 | S28  
1960

New BTs - 16" W.Oak bears S.13°E., 16.6 ft. scribed ¼ S28 CSBT  
8" W.Oak bears S.66°W., 58.1 ft. scribed ¼ S29 CS BT

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - Kody Inda - 8/20/2007 - C.S. File 67/24-7

-----  
Found - 2½" brass cap properly marked bent over touching ground.  
16" now 14" dia., x 2 ft. tall burnt Oak stump no marks fd., bears S.13°E., 16.6 ft. (agrees w/rec) 1960 BT  
8" now 14" dia., W.Oak, no marks visible, bears S.66°W., 58.1 ft. (agrees w/rec.) 1960 BT.  
Orig. 16" W.Oak, now fragments of burnt stump in large root hole, bears N.54°E., 35.4 ft. (agrees w/1960 rec) Orig. BT  
New - Referenced plumb position of BC/IP, removed & set new 2½" dia., brass cap on 1¼" O.D. x 30" iron pipe, in referenced position. BC projects 6" above ground - cap mkd: DOUGLAS CO. SURVEYORS  
T24S R5W  
¼  
S 29 | S 28  
2007

No trees or decent stumps exist within reasonable dist. from corner.

Note - Lies on West facing slope in area that was clearcut & burned.  
Compass decl. 16¼°E.