

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3113)

-----  
Set post cor. to secs. 8, 9, 16 and 17, from which  
A W.Oak 8" dia., bears N.85°W., 39 lks.  
A Y.Oak 20" dia., bears S.47°W., 87 lks.  
A Y.Oak 12" dia., bears S.45°W., 40 lks.  
A W.Oak 12" dia., bears N.52°E., 55 lks.

Survey by Don E. Garrett - For: A.J. Standley - April 1970  
M 39-47

-----  
Found - Orig. BT, N.85°W., 39 lks., fd. old scribing.  
Orig. BT, N.52°E., 55 lks., fd. old scribing.  
New BTs - 6" W.Oak S.19¼°E., 12.7 ft. mkd. T24S R5W S16 BT  
9" W.Oak S.64 3/4°W., 16.8 ft. "T24S R5W S17 BT"  
6" W.Oak N.45°W., 12.5 ft. mkd. T24S R5W S8 BT.  
13" W.Oak N.24°E., 20.9 ft. mkd. T24S R5W S9 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Vince Perron, crew - April 22, 1970 - C.S. File 49/124-106

-----  
Found - 5/8" I.rod set by Garrett.  
Orig. 8" now 14" W.Oak N.85°W., 25.7 ft alive - open & scribe visible (OBT)  
Orig. 12" now 16" W.Oak N.52°E., 36.3 ft. alive - open blaze decayed - reverse Axe notch (OBT)  
Set 1" IP & Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 5 W  
S 8 | S 9  
S 17 | S 16  
1970

Reset iron rod alongside.  
We add "CS" to the new BTs scribed by Garrett.  
Fd as recorded by Garret.  
Corner lies in E-W fence about 100 ft. E. of creek, 1 ft. wide.

Fd. Ok by Neil Hibbs, June 2005 - M146-21  
Fd. Ok by Neil Hibbs, 8/2021 - M178-37