

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3110)

-----  
Set ¼ sec. post, from which  
A W.Oak 16" dia., bears N.3½°E., 42 lks.  
A W.Oak 12" dia., bears S.24°E., 69 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - March 1960 - C.S. File 49/124-35

-----  
Found - Orig. 12" now 24" Oak, stump, S.24°E., 45.5 ft. I open and find good scribing "BT"  
Orig. 16" now 24" W.Oak snag, shows orig. scribing "BT", bears N.3½°E., 27.7 ft. This tree has been rescribed, probably by Theil.

Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 5 W  
¼  $\frac{S\ 28}{S\ 33}$   
1960

New BTs -6" W.Oak bears N.53°E., 23.3 ft. scribed ¼ S28 CSBT  
7" W.Oak bears S.30°E., 24.2 ft. scribed ¼ S33 CSBT  
N-S fence is 2 ft. East.

FD. OK - Wilcox, Harvey - Aug. 1995 - 1996-001 A&B

Fd. ok by Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 8/21/2007 - C.S. File 67/24-8