TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3114-15)

Set ¼ sec. post, from which
A W.Oak 18" dia., bears S.52½°E., 43 lks.
A Y.Oak 12" dia., bears N.19°W., 99 lks.

Survey by Don E. Garrett - For: A.J. Standley - April 1970 M 39-47

Set 5/8" Iron Rod. (Prorated ¼ corner)
Established BTs:
10" W.Oak N.19°E., 17.7 ft. scribed ¼ S4 BT.
7" B.Oak S.41¾°W., 38.2 ft. scribed ¼ S9 BT.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 7/12/2007 - C.S. File 67/21-41

Fd as per record

David Edwards - For: Roseburg Resources - 3/2020 - M176-69

Condition report only
Found - ⅝" IR and BTs per M39-47
13" dia. Oak bears N.19°E., 17.7'
13" dia., Oak bears S.41¾°W., 38.2'
Both with healed blazes.

Fd. as per rec. 3/2022 - B. Heichel - M180-63