

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3105)

Set post cor. to secs. 21, 22, 27 and 28, from which
A W.Oak 40" dia., bears S.55°E., 41 lks.
A W.Oak 20" dia., bears S.65°W., 78 lks.
A W.Oak 12" dia., bears N.35°W., 78 lks.
A W.Oak 10" dia., bears N.44°E., 68 lks.

Survey by William Barnes - For: Oliver Standley - Sept. 1977
M 65-45

Set 2" Brass cap, mkd. T24S R5W S21 S22 S28 S27 R.E. 2128,
from which
A 6" Oak bears N.23°W., 56.2 ft. scribed S21 T24S R5W BT
A 6" Oak bears S.61°E., 98.2 ft. scribed S27 T24S R5W BT

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- Kody Inda - 8/21/2007 - C.S. File 67/24-8

Corner falls in E-W fence line. Both BTs are Black Oaks. The
NW BT is most southerly stem of triple trunk B.Oak, rec dist.
measures to side center of said most southerly stem.

Fd. BC in fence by H. Wilcox, 7/2012 - M164-3