

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3108)

-----  
Set post cor. to secs. 3, 4, 9 and 10, from which

A W.Oak 14" dia., bears N.66°E., 87 lks.

A Y.Oak 12" dia., bears N.85¼°W., 110 lks.

A W.Oak 11" dia., bears S.72°W., 84 lks.

A W.Oak 8" dia., bears S.87 3/4°E., 90 lks.

-----  
Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Feb. 1960 - C.S. File 49/124-21

-----  
Found - W.Oak now 23", N.64½°E., (Rec. N.66°E.) 57.4 ft., chopped open and found old scribing.

B.Oak snag, now 23", N.87°W., (Rec. N.85¼°W., 72.6 ft., chopped open and found good scribing "B"

W.Oak now 21", S.70°W., (Rec. S.72°W.) 55.4 ft. Did not open. Blaze and scribe this tree "T24S R5W S9 CS BT"

W.Oak now 14", S.89½°E., (Rec. S.87 3/4°E.) 59.4 ft., did not open. Blaze and rescribe this tree "T24S R5W S10 CS BT"

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 5 W

S 4 | S 3

S 9 | S10

1960

Blaze and scribe new trees:

9" W.Oak N.21°E., 7.2 ft. scribed T24S R5W S3 CSBT

10" W.Oak N.28°W., 14.5 ft. scribed T24S R5W S4 CSBT

-----  
Fd. OK by W. Rogers, Feb. 2000 - M134-23