

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3099)

Set post cor. to secs. 22, 23, 26 and 27, from which
A Y.Oak 16" dia., bears S.37½°W., 77 lks.
A Y.Oak 16" dia., bears N.45°W., 19 lks.
A Y.Oak 20" dia., bears N.44°E., 117 lks.
A W.Oak 24" dia., bears S.43°E., 298 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - March 1960 - C.S. File 49/124-41

Found - Orig. 20" now 26" B.Oak N.44°E., 77.2 ft., previously opened, shows good scribing "23S"
Orig. SE BT, now stump, no opened.
No trace of orig. NW or SW BT found.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 5 W
S 22 | S 23
S 27 | S 26
1960

New BTs -11" W.Oak bears S.27°W., 12.1 ft. scribed S27 T24S
R5W CS BT.
11" W.Oak bears S.80°E., 26.3 ft. scribed S26 T24S
R5W CS BT.
8" W.Oak bears N.70½°W., 18.7 ft. scribed S22 T24S
R5W CS BT.
7" B.Oak bears N.25°E., 18.3 ft. scribed S23 T24S
R5W CS BT.

Corner at fence corner, fences running East, West and North

FD. 1960 BTs to north are intact. Land has been cleared to South taking BTs - Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 8/29/2007 - C.S. File 67/24-15