

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3099-3100)

Set post cor. to secs. 14, 15, 22 and 23, from which
A Y.Oak 36" dia., bears S.56°W., 33 lks.
A W.Oak 14" dia., bears N.33°W., 170 lks.
A Y.Oak 12" dia., bears N.24°W., 237 lks.
No other tree near.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - March 1960 - C.S. File 49/124-25

Found - Orig. 12" now 30" B.Oak N.24°W., 156.4 ft. I open and find good scribing "W"
Find stump hole and remains of large Oak, S.56°E., 21.8 ft. (Rec. S.56°W., 21.8 ft.)
No trace of orig. NE BT found.

Sec. Cor. 6.0 ft. southerly of fence corner, fences running westerly and northerly.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 5 W
S 15 | S 14
S 22 | S 23
1960

New BTs -14" W.Oak bears N.58°E., 45.5 ft. scribed S14 T24S
R5W CS BT.
14" W.Oak bears S.21°E., 63.8 ft. scribed S23 T24S
R5W CS BT.
10" W.Oak bears S.57°W., 49.6 ft. scribed S22 T24S
R5W CS BT.
16" W.Oak bears N.54°W., 40.0 ft. scribed S15 T24S
R5W CS BT.