

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35; & 2 T25-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder, Contract #31 dated April, 1853 (DCSO Records, Vol. 7 Page 3086)

Set ¼ Sec. post, from which
A Y.Oak 10" dia. bears S.28°E., 68 lks.
A Y.Oak 10" dia. bears N.68°E., 31 lks.

G.G. Stewart, Deputy - A.A. Thiel; Charlie; R.R. Clarke;
T.J. Medley; Roy Medley - January 1922 - Volume 3 Pg. 110

Found original BT which were decayed. Set a steel auto spring for corner & marked a 14" W.Oak bearing N.88°E., 26.7 ft. and a 10" B.Oak S.28°E., 44.8 ft.

James W. Byron, Deputy - Milo Godfrey; Clete Putnam;
March 17, 1960 - C.S. File 49/124-32

Found - 14" now 20" B.Oak N.88°E., 26.7 ft. I open & find good reverse scribing "T".
Auto spring dozed out of ground by near corner.
Set brass cap at cor. mkd: County Surveyor's ¼ S 35 T24S
Office 1960 S 2 T25S
New BTs- 10" W.Oak bears N.46°E., 15.0 ft. scribed ¼ S35 CS BT.
8" R.Fir bears S.58°E., 41.6 ft. scribed ¼ S2 CSBT.
E.W. fence 8 ft. South.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause
- Sept. 24, 1997 - C.S. 64/78-6

Mon. Fd.- 2½" dia. brass cap on a 1½" O.D. iron pipe protrudes 11" above ground. (1960)
Accessories Fd. -
14" W.Oak now 23" dia. B.Oak with a fully healed previously opened blaze, bears N.88°E., 26.7' (agrees with rec.)
10" now down and rotted 6" dia. Oak root hole, bears N.46°E., 15' (agrees with rec.) 1960 - no scribing or blaze found.
8" now down and rotted 5" dia. D.Fir, no scribe or blaze found, root hole bears S.58°E., 41.6' (agrees with rec.). 1960

Cont. next page

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35; & 2 T25-5

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New Accessories -

8" dia. W.Oak, double blazed and scribed "¼ S35
CS BT", bears N.64°W., 12.1'.

6" dia. W.Oak, double blazed and scribed "¼ S2
CS BT", bears S.76°E., 48.6'.

3" dia. W.Oak, double blazed and scribed "X
BT", bears S.7½°E., 20'.