

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3099)

Set ¼ sec. post, from which
A W.Oak 18" dia., bears N.7°W., 90 lks.
A Y.Oak 20" dia., bears S.48°W., 165 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - March 1960 - C.S. File 49/124-40

Found - W.Oak, nearly dead, now 25", N.7°W., 59.4 ft. This tree has been opened previously, good scribe "S"
Oak, dead and down, S.48°W., 108.9 ft. Did not open
Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 5 W
¼ $\frac{S\ 23}{S\ 26}$
1960

Blaze and scribe new BTs:
8" W.Oak S.75°W., 11.0 ft. mkd. ¼ S26 CS BT.
10" W.Oak N.59°E., 8.7 ft. mkd. ¼ S23 CS BT.
Corner falls in East and West fence line.

FD. 1960 BT to north is intact, has been cleared to South - Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 8/29/2007 - C.S. File 67/24-15