

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 7 Page(s) 3089)

Set ¼ sec. post, from which
A W.Oak 20" dia., bears S.85 ¾°E., 180 lks.
A W.Oak 26" dia., bears S.75°W., 206 lks.

G.G. Stewart, Deputy - Wit: T.J. Medley; R.R. Clarke; Roy Medley - Jan. 20, 1922 - Vol. 3 Page 110 (and "old" corner book, page 44)

Original BT present and do not check field notes. Rest cor. proportioning error. Reset with Cedar post with pile of rocks around it.
12" B.Oak N.85°W., 147.0 ft.

1943 - Frear set 1" x 30" I.Pin in mound of rock.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey and Clete Putnam - March 4-7, 1960 - C.S. File 49/124-30

Found - Orig. 26" now 40" W.Oak S.75°W., 154 ft. (Rec. S.75°W., 136 ft), shows old scars. I do not open.
Find now 30" W.Oak S.85 ¾°E., 136 ft. (Rec. S.85 ¾°E., 118.8 ft.), shows scars, I open but do not find scribing.
Mound of stone and ¾" Iron rod at corner and Stewart's B.Oak BT, now overgrown, but shows good scar. I do not open. I find bearing to be N.82°W. (Stewart, N.85°W.) Distance OK.
I do not set brass cap at corner but scribe new BT:
8" W.Oak bears N.30°E., 11.3 ft. scribed ¼ S36 CS BT.

David Edwards - For: Baxter Cattle Co. - 3/2016 - M170-60

Found - ¾" iron rod (bent)
19" W.Oak with healed blaze bears N.30°E., 11.3'
32" W.Oak with healed blaze bears S.86°E., 136.0'