

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3091)

-----  
Set post cor. to secs. 23, 24, 25 and 26, from which  
A W.Oak 28" dia., bears S.58°W., 110 lks.  
A W.Oak 16" dia., bears N.70°W., 176 lks.  
A W.Oak 24" dia., bears N.14°E., 340 lks.  
A Y.Oak 12" dia., bears S.9°E., 98 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey, S.A. Bilow - April 3, 1959 - C.S. File 49/124-5

-----  
Found - 2" x 15" x 8" stone at corner.  
Orig. 28" W.Oak, now 30" snag, previously opened, center mostly rotted, shows good scribing "BT".  
I find depression that checks bearing and distance for orig. SE BT.

No trace of other orig. BTs found.  
Set brass cap alongside corner stone marked:  
County Surveyors Office

T24S R5W  
S 23 | S 24  
S 26 | S 25  
1959

New BTs -6" W.Oak bears S.13°E., 10.4 ft. scribed S25 T24S  
R5W CS BT.  
9" W.Oak bears N.28½°E., 24.1 ft. scribed S24 T24S  
R5W CS BT.  
8" W.Oak bears S.14°W., 14.5 ft. scribed S26 T24S  
R5W CS BT.  
8" W.Oak bears N.79½°W., 31.2 ft. scribed S23 T24S  
R5W CS BT.

Corner 1 ft. East of N-S fence.

Found OK by C. Sweeden, Feb. 1998 - M 124-72

Fd as per rec. except 8" W.Oak N.79½°W., 31.2 ft. now gone - Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 8/22/2007 - C.S. File 67/24-11

Fd. as per M124-72, 3/2016 - M170-60 by D. Edwards