

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3092)

-----  
Set post cor. to secs. 13, 14, 23 and 24, from which  
A W.Oak 24" dia., bears N.80°E., 69 lks.  
A W.Oak 9" dia., bears S.41°E., 132 lks.  
A Y.Oak 18" dia., bears S.50°W., 84 lks.  
A Y.Oak 18" dia., bears N.82½°W., (dist. lost)

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - March 1960 - C.S. File 49/124-28

-----  
Found - Orig. 9" now 20" W.Oak S.41°E., 87.1 ft. I open and find good scribing "W"  
Orig. NE BT, now shell of old stump only.  
No trace of orig. NW nor SW BTs found.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 5 W  
S 14 | S 13  
S 23 | S 24  
1960

New BTs -6" W.Oak bears S.62°E., 19.6 ft. scribed S24 T24S R5W CS BT.  
7" W.Oak bears S.35°W., 8.2 ft. scribed S23 T24S R5W CS BT.  
7" W.Oak bears N.52°W., 16.7 ft. scribed S14 T24S R5W CS BT.  
Red Fir bears N.17½°E., 125.4 ft. scribed S13 T24S R5W CS BT.

Carl Sweeden, surveyed for A.Zuppan, Feb. 1998 - M 124-72

-----  
Condition report only

Found - DCSO Brass cap loose in ground at fence corner.  
6" W.Oak, S.62°E., 19.6 ft. - now gone.  
9" W.Oak, S.35°W., 8.2 ft. - scar visible  
10" W.Oak, N.52°W., 16.7 ft.  
28" R.Fir, N.17°30'E 125.4 ft. - scar visible

Note - All trees listed are tagged.

Fd. as per record - Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 8/22/2007 - C.S. File 67/24-11