

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3094)

-----  
Set post cor. to secs. 11, 12, 13 and 14, from which  
A Y.Oak 24" dia., bears S.35°E., 84 lks.  
A Y.Oak 20" dia., bears N.62½°E., 78 lks.  
A Y.Oak 18" dia., bears N.24°W., 84 lks.  
A Y.Oak 26" dia., bears S.42½°W., 95 lks.

Survey by Victor McLind - For: Bernard Nerell - June 1973 - M 49-24

-----  
Set by double proportionate measurement.  
Set 5/8" iron rod.  
BTs - 4" B.Oak bears N.54°E., 61.3 ft.  
14" Madrone bears S.61 3/4°E., 67.3 ft.  
16" Madrone bears S.82¼°W., 49.7 ft.  
12" W.Oak bears N.63¼°W., 86.2 ft.  
Section corner bears S.32°W., 8.4 ft. from an 8" W.Oak at a 4 way fence corner.

Fd as per rec. except Both madrone BTs now gone - Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 8/22/2007 - C.S. File 67/24-11