

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3095)

Set post cor. to secs. 1, 2, 11 and 12, from which

- A Y.Oak 24" dia., bears S.67°E., 127 lks.
- A W.Oak 9" dia., bears N.25°E., 97 lks.
- A Y.Oak 10" dia., bears N.68°W., 27 lks.
- A W.Oak 40" dia., bears S.42½°W., 41 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - March 1960 - C.S. File 49/124-23

Found - Orig. 9" now 20" W.Oak, shows good scar. I do not open. Bears N.25°E., 64.0 ft.

- Orig. 10" now 20", down, mostly rotted, B.Oak, N.68°W., 17.8 ft., good reverse scribing found "T 1"
- Orig. 40" now 44" remains of Oak stump, shell only left, S.42½°W., 27.1 ft.
- Orig. 24" now B.Oak snag, face and side rotted, no scribing found, S.67°E., 83.8 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T	24	S	R	5	W
S	2	S	1		
S	11	S	12		
					1960

- New BTs -8" W.Oak bears N.72°W., 4.9 ft. scribed S2 T24S R5W CS BT.
- 12" W.Oak bears S.39°E., 18.8 ft. scribed S12 T24S R5W CS BT.
- 8" W.Oak bears S.18°W., 43.7 ft. scribed T24S R5W S11 CS BT.
- Orig. 10" now 20" W.Oak bears N.26°E., 63.5 ft. I do not rescribe, BT is OK.

Douglas County Surveyors Office - Randall Smith, Stephen Flause, Terrie Franssen, crew - March 4, 1991 - C.S File 64/13-5

CONDITION REPORT ONLY

Found - A 2½" dia., 1960 DCSO brass cap on a 1¼" O.D. Iron pipe protrudes 14" above ground.

- 9" now 23" dia. W.Oak with a fully healed blaze, bears N.26°E., 64.5 ft. Orig. BT.
- 40" now 32" dia. 1 ft. high Oak stump with a rotted out center, bears S.42½°W., 27.1 ft. Orig. BT.

No other original BTs found.

(Cont. Next Page)

TOWNSHIP 24 RANGE 05 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" now 11" dia. W.Oak with a fully healed blaze,
bears N.72°W., 4.9 ft. (1960 BT)
12" now 16" dia. W.Oak with a fully healed blaze
bears S.39°E., 18.8 ft. (1960 BT)
8" now 13" dia. W.Oak with a fully healed blaze
bears S.18°W., 43.7 ft. (1960 BT)
Corner lies at the end of a South running fence line, near
the intersection of dirt logging road.

Fd as per rec. by Douglas Co. Surveyors Office - Stephen
Flause, John Pike, Kody Inda - 8/21/2007 - C.S. File 67/24-8

Fd. DCS0 BC/IP by DCS0 5/2014 - M167-77