

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Tsp. Cor. (SW Cor. Sec. 31)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 8 Page 3130)

Set post cor. to Tps. 24 & 25 South & bet. Rgs. 6 & 7,
from which:

- A Fir 36" dia. bears S.80½°W., 89 lks. dist.
- A Fir 30" dia. bears N.7½°W., 122 lks. dist.
- A Fir 28" dia. bears N.56 3/4°E., 97 lks. dist.
- A Fir 44" dia. bears S.18°E., 70 lks. dist.

Bureau of Land Management dependent resurvey -
Lynn Roseberry - Group #645 - Survey, August 3 - Sept. 5
1967 - (DCSO records, Volume 36 Page 14941)

Point for the cor. to tps. 24 and 25 S., R. 6 W., at record
dist. in latitude from the cor. of secs. 30 & 31 only on the
west boundary of T.24S R6W; and at record distance in
departure from the cor. of secs. 5, 6, 31 and 32; there is
no remaining evidence of the original corner.

Set an iron post 28" long 2½" dia. 24" in the ground, with
brass cap mkd:

| | |
|--------|-------------|
| | T 24 S |
| | R 6 W |
| T 25 S | <u>S 31</u> |
| R 7 W | S 6 |
| S 1 | T 25 S |
| | 1967 |

from which

- A Fir, 14" dia. bears N.20¼°E., 83 lks. dist. mkd.
T24S R6W S31 BT.
- A Fir, 10" dia. bears S.57°E., 26 lks. dist. mkd.
T25S R6W S6 BT.

From this point, the ¼ sec. cor. of secs. 1 and 6, Tps.
25S.; Rs. 6 & 7.; bears S.3°44'E., 46.37 chs. dist.,
described in the notes of the dependent resurvey in
T.25S., R7W. of this Group.

DCSO-GIS Corner visitation - 5/12/2004 - Typed: 1/21/2011 -
C.S. File 67/33-1

Monument - 2" IP/BC
Comment - OK