

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors,
under Contract #31 dated April 7, 1853 (DCSO records Vol. 8
Page(s) 3130)

Set ¼ sec. post, from which
A Fir 12" dia., bears S.87°E., 44 ks. dist.
A Fir 8" dia., bears S.3°W., 59 lks. dist.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under
Group #645 Surveyed, Aug/Sept. 1967 - (DCSO records Vol. 36
Page(s) 14942)

Point for the ¼ sec. cor. of sec. 31 only, at proportionate
distance; there is no remaining evidence of the original
corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd:

	T 24 S
	S 31
	1/4 R 6 W
	1967

from which
A Fir 8" dia., bears N.1½°E., 217 lks. dist., mkd. ¼ S31
BT.
A Fir 6" dia., bears S.50½°E., 22 lks. dist., mkd. ¼ S31
BT.

Survey by Mark Smalley - For: Roseburg Forest Products - Oct.
1994 - C.S. File 63/154-22

Found - 1967 BLM brass cap.
8" Fir N.1½°E., 143.2 ft. now healed 12" Fir.
6" Fir S.50½°E., 14.5 ft. now healed 14" Fir.
New BTs - 6" Fir N.26°E., 15.3 ft. "¼ S BT" scribed.
11" Fir S.67°W., 15.3 ft. "¼ S BT" scribed.