

PRIMARY CORNER DESCRIPTION Cor. for Secs. 30 & 31 only, W. bdy.

| | |
|------------|------------------|
| Alias_____ | Description_____ |
| Alias_____ | Description_____ |
| Alias_____ | Description_____ |
| Alias_____ | Description_____ |

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3129)

Set post cor. to secs. 30, 31, 25 and 36, from which
A Fir 20" dia., bears N.23°E., 37 lks. dist.
An Ash 14" dia., bears N.50°W., 34 lks. dist.
An Ash 6" dia., bears S.52½°W., 45 lks. dist.
An Ash 14" dia., bears S.3°E., 36 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3159-60)

Post gone, reestablish same by setting a Fir post, 4 ft. long, 4" sq., 24" in the ground, mkd. T24S S30 on NE.; R6W S31 on SE.; R7W S36 on SW.; S25 on NW. faces, with 1 notch on S. and 6 notches on E. edges, from which
A Fir 20" dia., bears N.23°E., 37 lks. dist. mkd. T24S R6W S30 BT.
A Fir 14" dia., bears S.3°E., 36 lks. dist. mkd. T24S R6W S31 BT.
A Fir 6" dia., bears S.52½°W., 45 lks. dist., mkd. T24S R7W S36 BT.
A Fir 14" dia., bears N.50°W., 34 lks. dist. mkd. T24S R7W S25 BT.
(Pages 3236-37, Whipple found corner and on Page 3275, says he destroyed all marks referring to secs. 25 and 36 on this old corner)

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #645 Surveyed, Aug/Sept. 1967 - (DCSO records Vol. 36 Page(s) 14942-43)

The cor. of secs. 30 and 31 only, determined at record bearing and distance from the original bearing trees:
A burned Fir 39" dia., bears N.23°E., 37 lks. dist., with a healed blaze.
A burned and sawed Fir stump 31" dia., bears S.3°E., 36 lks. dist., with scribe marks 4 S BT visible on opened blaze.
A root hole, bears S.52½°W., 45 lks. dist.
A burned and shattered Fir stump 25" diam., bears N.50°W., 34 lks. dist., with lower portion of burned blaze visible.

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Cor. for Secs. 30 & 31 only, W. Bdy.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd:

| | |
|--------|--------|
| T 24 S | T 24 S |
| R 7 W | R 6 W |
| S 36 | S 30 |
| | S 31 |
| 1967 | |

from which a new bearing tree
A Fir 13" dia., bears S.68°E., 110 lks. dist., mkd. T24S
R6W S31 BT.
Corner falls in head of ravine, drains SE.

Survey by Mark Smalley - For: Roseburg Forest Products - Oct.
1994 - C.S. File 63/154-24

CORNER REPORT

Found - 1967 BLM brass cap and iron pipe.
25" Fir N.50°W., 22.4 ft., rotten stump, (OBT 1853)
39" Fir N.23°E., 24.4 ft., burnt stump (OBT 1853)
31" Fir S.3°E., 23.8 ft., stump (OBT 1853)
16" Fir S.68°E., 72.6 ft., healed (1967 BLM)
47" Fir N.35 3/4°W., 9.4 ft. healed (1984 I.Paper)