

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3128-29)

Set ¼ sec. post, from which
A Fir 12" dia., bears S.58½°E., 72 lks. dist.
A Fir 15" dia., bears S.29°W., 39 lks. dist.

A.R. Evans - Wit: M.E. Evans, G.E. Johnson - May 10, 1953
C.S. File 41/246-2

At corner point, set ½" Iron pipe with 4' x 4" x 36" scribed
Fir stake alongside, from which
Old BT, 12" Fir bears S.58½°E., 72 lks.
New BT, 20" Fir N.18°W., 28.5 ft.

BLM dependent resurvey by Joseph S. Gawron under Group #464
surveyed May/June 1962 (DCSO records Vol. 31 Page(s) 13116)

The ¼ sec. cor. of sec. 19 only, as determined from the one
remaining original bearing tree:
A Fir 30" dia., bears S.58½°E., 72 lks. dist., mkd. ¼ S BT
At the corner point
Set an iron post, 30" long, 2½" dia., 28" in the ground, with
brass cap mkd: T 24 S R 6 W
 | ¼ S19
 1962

from which
A W.Fir 10" dia., bears N.34°E., 124 lks. dist., mkd. ¼
S19 BT.
A W.Fir 8" dia., bears S.69°E., 151 lks. dist., mkd. ¼ S19
BT.