

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T24-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3128)

Set post cor. to secs. 18, 19, 13 and 24, from which
A Fir 15" dia., bears S.67°E., 238 lks. dist.
A Fir 18" dia., bears N.87½°E., 287 lks. dist.
A W.Oak 12" dia., bears N.40°W., 37 lks. dist.
A W.Oak 5" dia., bears S.44°W., 103 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3164-65)

The Sec. cor., Post gone, reestablish same by setting a Fir post, 4 ft. long, 4" sq., 24" in the ground, mkd. T24S S18 on NE.; R6W S19 on SE.; R7W S24 on SW., and S13 on NW. faces with 3 notches on S. and 6 notches on E. edges, from which, the original bearing trees are as follows:

- A Fir 18" dia., bears N.87½°E., 287 lks. dist. This tree has fallen down and is much decayed.
- A Fir 15" dia., bears S.67°E., 238 lks. dist. This tree has been burned down, but the stump is standing, showing scars where marks were made. Marks burned out.
- A W.Oak 12" dia., bears N.40°W., 37 lks. dist., mkd. T24S R7W S13 BT.
- A W.Oak 5" dia., bears S.44°W., 103 lks. dist. This tree has fallen down and is much decayed.

Marked new bearing trees as follows:

- A Fir 38" dia., bears N.86°50'E., 337 lks. dist. mkd. T24S R6W S18 BT.
- A Fir 20" dia., bears S.66°E., 236 lks. dist. mkd. T24S R6W S19 BT.
- A W.Oak 8" dia., bears S.62°25'W., 287 lks. dist. mkd. T24S R7W S25 BT.

A.R. Evans - Wit: G.E. Johnson, M.E. Evans - May 9, 1953 - C.S File 41/246-1

Found - 40" Fir snag, N.87½°E., 287 lks.
At corner point, Set ½" I.Rod with a 4"x4"x36" Oak post alongside, from which
10" Fir bears N.33°E., 20.1 ft.
9" Madrone bears S.37°E., 39.6 ft.
6" B.Oak bears S.6°W., 29.2 ft.
4" B.Oak bears N.53°W., 26.7 ft.

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T24-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - James Byron, Deputy - Crew,
Milo Godfrey; S.A. Bilow - crew - March 1959 - C.S. File
49/83-1

Found - Orig. Whipple BT, 20" now 34" down Fir, S.66°E.,
155.8 ft. Most of old face burned but I do find
good scribing "R".
No trace of orig. SW or NE BTs.
Shell of Oak stump that checks bearing and distance
for NW BT.

Set Brass cap at cor. mkd:

County Surveyors Office

T 24 S
R7W S 13 | S 18 R6W
S 24 | S 19
1959

New BTs -6" W.Oak bears N.81°E., 62.8 ft. scribed S18 T24S
R6W CS BT.
6" W.Oak bears N.42°W., 45.6 ft. scribed S13 T24S
R7W CS BT.
4" W.Oak bears S.69°W., 28.2 ft. scribed S24 T24S
R7W CS BT.
6" R.Fir bears S.11½°E., 38.5 ft. scribed S19 T24S
R6W CS BT.

This corner renewed by Evans, 1953, however at this time, I
find no evidence on snag used by Evans to indicate it to be
a BT. Today, I talked to Mr. McHughill, who was with Evans
just prior to the 1953 renewal. He states that there was no
evidence the snag used by Evans was a BT at that time. Also,
it appears Evans used the distance recorded by Elder and Gile
for a BT recorded by Whipple. Evans corner bears N.69°E.,
99.8 ft. I destroy all evidence of his corner.
Brass cap bears N.28°E., 33 ft. from fence corner, fences
running N. & S. and West.

BLM dependent resurvey by Joseph S. Gawron under Group #464
surveyed May/June 1962 (DCS0 records Vol. 31 Page(s) 13117-
18)

The Sec. cor., perpetuated with a DCS0 survey mark, an iron
post, 1½" dia., firmly set, with properly mkd. brass cap.
from which the remaining original bearing trees:

A Fir, dead and down, 34" dia., bears S.66°E., 236 lks.
dist. mkd. R on a chopped and burned face. This tree
mkd. by Whipple in 1891.

A shell of an Oak stump bears N.40°W., 37 lks. dist.,
(Elder & Gile BT.)

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T24-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and trees mkd. by the County Surveyor
A W.Oak 7" dia., bears N.81°E., 95 lks. dist., mkd. S18
T24S R6W CS BT.
A Fir 7" dia., bears S.11½°E., 59 lks. dist., mkd. S19
T24S R6W CS BT.
A W.Oak 5" dia., bears S.69°W., 42½ lks. dist., mkd. S24
T24S R7W CS BT.
A W.Oak 7" dia., bears N.42°W., 69 lks. dist., mkd. S13
T24S R7W CS BT.
and new bearing trees
A Fir 12" dia., bears N.73°E., 189 lks. dist., mkd. T24S
R6W S18 BT.
A W.Oak 6" dia., bears S.77°E., 48½ lks. dist., mkd. T24S
R6W S19 BT.
A Fir 6" dia., bears S.9°W., 129 lks. dist., mkd. T24S R7W
S24 BT.
A W.Oak 7" dia., bears N.49°W., 107 lks. dist., mkd. T24S
R7W S13 BT.

Fd. OK, Dec. 1992, R.Dolan, M 116-38
Fd. OK, Oct. 1995, D.Bentz, M 123-6