

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7; & 12 of T24-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Pg. 3127)

-----  
Set 1/4 Sec. post from which:

- A Fir, 40" dia., bears S.55°E., 30 lks. dist.
- A Fir, 13" dia., bears S.72°W., 25 lks. dist.

BLM Resurvey by W. Rogers & R. Browning - May/June 1993 under group #1687, (DCSO records Vol. 51 Pg. 19536)

-----  
The 1/4 sec. cor. of secs. 7 and 12, reestablished by proportionate measurement by the International Paper Co. in 1971 (as per records obtained from International Paper Co.). There is no remaining evidence of the original corner, therefore, this position is accepted as the corner, monumented with an iron pipe, 1 in. dia., firmly set, projecting 20 ins. above ground, from which the reference trees by International Paper Co.:

Found Bearing Trees -

- A Fir, 13" dia., bears N.33½°E., 15 lks. dist., with a metal International Paper Co. Tag.
- A Fir, 18" dia., bears N.32°W., 31 lks. dist., with a metal International Paper Co. Tag.

Set - A stainless steel post, 28" long, 2½" dia. 25 " in the ground, with brass cap mkd.

T24S  
R7W R6W  
1/4  
S 12 S 7  
1993

New Bearing Trees -

- A Fir, 15" dia., bears N.73°E., 15½ lks., mkd. "¼ S7 BT"
- A Fir, 12" dia., bears S.17°W., 30 lks., mkd. "¼ S12 BT"

Note - Deposit the iron pipe inside and a white "DEEP-1" magnetic marker at base of stainless steel post.