

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T24-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3127)

-
- Set post, cor. to secs. 6, 7, 1 and 12, from which
- A Fir 15" dia., bears S.89°W., 62 lks. dist.
 - A Fir 12" dia., bears N.83°W., 87 lks. dist.
 - A Fir 12" dia., bears N.16°E., 21 lks. dist.
 - A Fir 30" dia., bears S.89 3/4°E., 64 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3189)

The Sec. cor. to 6, 7, 1 and 12, post gone. Set a Chestnut post, 4 ft. long, 6" sq., 24" in the ground, mkd. T24S S6 on NE.; R6W S7 on SE.; R7W S12 on SW.; and S1 on NW. faces, with 5 notches on the S. and 6 notches on the E. edges, from which original bearing trees are as follows:

- A Fir 30" dia., bears S.89 3/4°E., 64 lks. dist., mkd. T24S R6W S7 BT.
- A Fir 15" dia., bears S.89°W., 62 lks. dist., mkd. T24S R7W S12 BT.
- A Fir 12" dia., bears N.83°W., 87 lks. dist., mkd. T24S R7W S1 BT.

The other bearing tree is gone.

I marked:

- A Dogwood, 4" dia., which bears N.75°E., 9 lks. dist., mkd. T24S R6W S6 BT.

BLM resurvey by Orville N. Eggen, Cadastral Surveyor, under Group #244, surveyed May/Aug. 1957 - (DCSO records Vol. 30 Page(s) 12618-19)

The Sec. Cor., determined at record bearing and distance from the two remaining original bearing trees:

- A Fir 55" dia., bears S.89 3/4°E., 64 lks. dist., mkd. with a healed blaze.
- A Fir 44" dia., bears S.89°W., 62 lks. dist., with scribe marks B T visible on an opened blaze.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 18" in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd:

T 24 S
R 7 W R 6 W
S 1 S 6
S 12 S 7
1957

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T24-7

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

from which

A Fir 16" dia., bears N.72°E., 94 lks. dist., mkd. T24S R6W S6 BT.

A Fir 55" dia., bears S.89 3/4°E., 64 lks. dist., mkd. T24S R6W S7 BT.

A Fir 44" dia., bears S.89°W., 62 lks. dist., mkd. T24S R7W S12 BT.

A Maple 12" dia., bears N.53°W., 52 lks. dist., mkd. T24S R7W S1 BT.

Cor. Fd. and tied by Floyd Brooks, BLM resurvey April/May 1964 DCSO records, Vol. 32 Page 13492)

BLM resurvey by Dale Bedell - May 1992 thru April 1993 under group #1637. (DCSO records Vol. 51 Pg. 19540)

Found - Iron post, 2" dia. firmly set, projecting 14" above the ground, in a mound of stone, 3 ft. base to top, with brass cap properly marked.

Bearing Trees found -

A Fir, 57" dia., bears S.89 3/4°E., 64 lks. dist., no marks visible on open blaze.

A rotted Fir stump, 40" dia., bears S.89°W., 62 lks. dist., no marks visible.

A Fir, 21" dia., bears N.71½°E., 92 lks. dist., eith healed blaze. (record, N.72°E., 94 lks.)

New Bearing Trees -

A Fir, 14" dia., bears S.44¼°W., 75 lks. dist., mkd. "T24S R7W S12 BT"

A Maple, 26" dia., bears N.23½°W., 68 lks. dist., mkd. "T24S R7W S1 BT"

Fd. OK. by W.Rogers 6/93 - DCSO records Vol. 51 Pg. 19537

Fd. OK. by M. Smalley - 12/96 - C.S. 65/15-6E