

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3160)

Set Yew post, 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which
A Fir 55" dia., bears N.66°45'W., 47 lks. dist. mkd. 1/4 S BT.
A Cedar 30" dia., bears S.58°30'E., 133 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S. Bilow - April 22, 1958 - C.S. File 49/83-11

Found - Orig. 30" now 36" Cedar S.58 1/2°E., 87.8 ft. I open and find scribe marks, negative, on rotted face. Rotted base of Fir stump that checks record dist. and brg. for orig. NW BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
1/4 S 30
S 31
1958

New BTs -9" R.Fir bears S.37°E., 23.7 ft. scribed 1/4 S31 CS BT
14" R.Fir bears N.77°E., 13.9 ft. scribed 1/4 S30 CSBT

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - Aug. 27, 1970 - C.S. File 52/102-9

Found - No trace of brass cap due to fill and debris from road construction sliding down hill.
Orig. 30" Cedar now 36" stump, S.58 1/2°E., 87.8 ft. find old axe work and parts of old blaze.
BTs from 1958 are both down and out of place. We are unable to determine exactly where they stood.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
1/4 S 30
S 31
1970

New BTs -12" Laurel S.50°W., 18.6 ft. mkd. 1/4 S31 CS BT.
8" Chinquapin N.55°W., 32.8 ft. mkd. 1/4 S30 CS BT.
Corner lies on very steep, northerly slope approx. 50 ft. East of road at sharp curve.

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Gary T. Smither - for: I.P. Timberlands - Oct 1995 - M122-70

Mon. Fd. - County Brass cap

Bt's Fd. - 18" Madrone (rec. Laurel), S.50°W 18.6', High
stumped (now sprouted) healed face old spike
side center and tagged.

15" Chinquapin, N.55°W. 32.8', healed face and
tagged.

New BT's - 7" Chinquapin, N.32°W. 20.8', scribed T24 R6 S30
¼ BT, dist. to spike side center. tagged.

15" D.Fir, S.26°E. 36.6', scribed T24 R6 S31 ¼
BT, dist. to spike side center. tagged.

Set property corner sign on aluminum post near
monument.

Fd. ok by Troy Rambo, May 2005 M148-8