

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3186)

Set Cedar post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd. ¼ S on N. face, from which
A Fir 21" dia., bears N.42°15'W., 10 lks. mkd. ¼ S BT.
A Fir 36" dia., bears S.51°W., 43 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Aug. 1959 - C.S. File 49/83-23

Found - Orig. 21" now mostly rotted Fir snag, N.42°15'W., 6.6 ft. no scribing.
Orig. 36" now shell of large Fir snag, good scribing, "S 11", S.51°W., 29.4 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
¼ $\frac{S}{S}$ $\frac{7}{18}$
1959
New BTs -18" Cedar bears N.14°E., 22.9 ft. scribed ¼ S7 CSBT
5" R.Fir bears S.47°E., 7.1 ft. scribed ¼ S18 CS BT.

Ken Hoffine - For: Lone Rock Timberland & Roseburg Resources - May 2014 - M168-11

Found - 1959 County cap 18" above ground.
30" cedar bears N.14½°E., 22.8 ft. (rec. N.14°E., 22.9 ft) well healed face and tag.
14" D.Fir bears S.44¾°E., 6.8 ft. (rec. S.47°E., 7.1 ft.) well healed face and tag.
Corner lies on steep west facing slope approx. 200 ft. east of draw.

Fd. as per M168-11 by D Edwards, 7/2016 - C.S. File 65/92-14