

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Pg 3190)

A Dogwood 6" dia. which I marked $\frac{1}{4}$ S on the North side for $\frac{1}{4}$ sec. cor., from which

A Cedar 15" dia., bears N.77°W., 7 lks. mkd. $\frac{1}{4}$ S BT.

A Fir 14" dia., bears S.22°40'E., 49 lks. mkd. $\frac{1}{4}$ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - March 1960 - C.S. File 49/83-27

Found - Orig. 14" now 30" R.Fir, S.22°40'E., 32.3 ft. I open and find good scribing " $\frac{1}{4}$ "

Orig. NW BT gone.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 6 W

$\frac{1}{4}$ $\frac{S}{S}$ $\frac{6}{7}$

1960

Corner near top of cut slope of logging road.

New BTs -17" Hemlock bears S.52°E. 39.3 ft scribed $\frac{1}{4}$ S7 CS BT

7" R.Fir bears N.72°E., 32.3 ft. scribed $\frac{1}{4}$ S6 CS BT.

Mark Smalley - for: Roseburg Forest Products - Dec. 5 1996 -C.S. 65/15-6C

Found - 1960 DCSO IPBC

18" Fir, N.72°E., 32.3' good - healed face

20" Hemlock, S.52°E., 39.3' good - healed face

28" rotting stump, S.22°40'E., 32.3' open face scribing visible - original BT.

New - 14" Fir, S.78°W., 44.5' scribed " $\frac{1}{4}$ S BT"

16" Fir, N.38°W., 44.8' scribed " $\frac{1}{4}$ S BT"

Robert Ward - Ron Rice & Josh Reed, crew - June 2010 - C.S. File 65/69-36

Found - DCSO BC (properly marked)

21" D.Fir bears N.72°E., 32.3' (healed face)

23" Hemlock bears S.52°E., 39.3' (healed face)

28" rotting stump bears S.22°40'E., 32.3' (visible scribing)

17" D.Fir bears S.78°W., 44.5' (healed face)

20" D.Fir bears N.38°W., 44.8' (healed face)