

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and 31 of T23-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2390)

Set 1/4 sec. post, from which
A Laurel 14" dia., bears N.10°E., 68 lks.
A Fir 40" dia., bears S.38°W., 53 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12648)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 2" dia., 10" in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd:
T23SR6W
1/4 S 31
S 6
T24S
1957

from which
A Fir 11" dia., bears N.39°W., 10 lks. dist., mkd. 1/4 S31 BT
A Fir 15" dia., bears S.65°W., 15 lks. dist. mkd. 1/4 S6 BT.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor under Group #244, surveyed April/May 1964 (DCSO Records, Vol. 32 Page(s) 13496-97)

Point for the 1/4 sec. cor. of 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

From this point, the 1/4 sec. cor. of secs. 6 and 31, erroneously reestablished by Eggen in 1957, bears South, 0.14 chs. dist., set, marked and witnessed as described in the official record. I remove the iron post, destroy the marks on the NW. bearing tree, and at the corner point

Reset the iron post, 36" long, 2" dia., 32" in the ground, with brass cap mkd: T 23 S R 6 W
1/4 S 31
S 6
T 24 S
1957

from which a new bearing tree
A Fir 20" dia., bears N.30°E., 29 lks. mkd. 1/4 S31 BT.
(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and 31 of T23-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

and a bearing tree mkd. by Eggen in 1957
A Fir 15" dia., bears S.27°W., 25 lks. dist., with a
healed blaze.

*(NOTE: BLM suspended survey Sept. 1983; Lifted suspension
Feb. 1985; and again suspended survey Feb. 1992. (BLM field
work pending)*

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W.
Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral
Surveyors; and Robert H. Browning, Surveying Technician -
under Group #'s 1266, 1637 and 1688, - surveyed June 9,
1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19452)

The ¼ sec. cor. determined at record bearing and distance
from the remains of an original bearing tree:

A fir snag, 57 ins. diam., bears S. 38° W., 53 lks. dist.,
with scribe marks ¼ S BT and a chaining notch visible
on opened blaze.

From this point, the ¼ sec. cor. of secs. 6 and 31,
erroneously reestablished by Brooks in 1964, bears S. 64° 59'
30" E., 2.090 chs. dist., monumented with an iron post, 2
ins. diam., firmly set, projecting 4 ins. above ground, with
brass cap marked and witnessed as described in the official
record. Remove the iron post, obliterate the marks on the
bearing trees, and at the true corner point:

Reset the iron post, 30 ins. long, 2 ins. diam., 26 ins. in
the ground, with brass cap mkd.

T23S R6W

S31

¼ ———

S6

T24S

1957

1993

from which new bearing trees

A fir, 19 ins. diam., bears S. 48° E., 42 lks. dist., mkd.
¼ S6 BT.

A fir, 20 ins. diam., bears N. 55° W., 27 lks. dist., mkd.
¼ S31 BT.

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and 31 of T23-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Mark Smalley - For: Roseburg Forest Products - Dec. 4, 1996
- C.S. 65/13-9G

Mon. Fd.- 1993 GLO IPBC
Bt's Fd.- 57" Fir, S.38°W., 53 lks. chopped into
19" Fir, S.48°E., 42 lks. good scribe visible
18" Fir, N.55°W., 27 lks. good scribe visible
New Bt's- 14" Fir, S.50°E., 38.9' scribed "¼ S BT"
18" Fir, N.12°E., 20.2' scribed "¼ S BT"

Robert Ward - Ron Rice & Josh Reed, crew - June 2010 - C.S.
File 65/69-35

Found - Brass cap (properly marked)
21" D.Fir rotten staub bears S.38°W., 35.0' (visible
scribing)
20" W.Fir bears S.48°E., 27.7' (visible scribing)
18" D.Fir now blow down,
15" D.Fir bears S.50°E., 38.9' (healed face)
20" D.Fir bears N.12°E., 20.2' (healed face)