

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3155-56)

-----  
Set post cor. to secs. 29, 30, 31 and 32, from which  
A W.Oak 20" dia., bears N.69½°E., 454 lks. dist.  
A W.Oak 13" dia., bears N.89°W., 68 lks. dist.  
A W.Oak 11" dia., bears S.46 3/4°E., 362 lks. dist.  
A W.Oak 13" dia., bears S.66 3/4°W., 50 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3159)

-----  
The established corner to secs. 29, 30, 31 and 32, Post gone, I reestablish same by setting Fir post 4 ft. long, 4" sq., 24" in ground mkd. T24S S29 on NE.; R6W S32 on SE.; S31 on SW.; S30 on NW. faces with 1 notch on the South and 5 notches on the E. edges, from which  
A W.Oak 20" dia., bears N.69¼°E., 454 lks. dist. mkd. T24S R6W S29 BT.  
A W.Oak 11" dia., bears S.46 3/4°E., 362 lks. dist. mkd. T24S R6W S32 BT.  
A W.Oak 13" dia., bears S.66 3/4°W., 50 lks. dist. mkd. T24S R6W S31 BT.  
A W.Oak 13" dia., bears N.89°W., 68 lks. dist. mkd. T24S R6W S30 BT.

Germond - Field Book 21 Page 16 - 1915

-----  
Set W.Oak post, from which new Wit. trees as follows:  
W.Oak 8" N.57°35'E., 84½ lks.  
W.Oak 6" N.36°22'W., 178 lks.  
R.Fir 7" S.2°04'E., 90 lks.  
R.Fir 12" S.11°57'W., 102 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S. Bilow - April 18, 1958 - C.S. File 49/83-13

-----  
Found - 2 BTs as recorded by Germond in 1915:  
7" R.Fir now 24" partly rotted stump, S.2°04'E., 59.4 ft. Good scribing visible.  
12" R.Fir now 30" partly rotted stump. I open and find good scribing "BT". Both BTs check bearing and distance.  
4" x 4" x 24" old scribed Oak stake. I do not believe it has been here long.  
(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

12" when scribed Fir stump for sec. corner. 1915+-.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 6 W  
S30|S29  
S31|S32  
1958  
New BTs -24" R.Fir N.54°W. 45.7 ft scribed S30 T24S R6W CS BT  
20" R.Fir N.15°E. 62.0 ft scribed S29 T24S R6W CS BT  
23" R.Fir S.13°W. 93.0 ft scribed S31 T24S R6W CS BT  
7" R.Fir S.64°E., 32.3 ft scribed S32 T24S R6W CS BT

---

Fd. Ok by Les Roberts - March 2000 - M134-38

---

Troy Rambo - For: Seneca Jones Timber Co. - 5/2005 - M148-8  
-----  
Found - A 1958 county brass cap, per C.S. File 49/83  
The record 24" fir - now a stump with a healed face.  
The record 20" fir - now a stump - no marks  
The record 7" fir - gone  
The record 23" fir(now 28") in good condition  
New - Scribed "S30 BT" on a 20" D.Fir - bears N.39°W.,  
11.8 ft.  
Scribed "S31 BT" on an 18" D.Fir - bears S.49°W.,  
10.0 ft.

---

2