

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3164)

Set a Cedar Post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 17, 18, 19 and 20, mkd. T24S S17 on NE.; R6W S20 on SE.; S19 on SW.; and S18 on NW. faces with 3 notches on S. and 5 on E. edges, from which
A Fir 14" dia., bears N.79°E., 77 lks. dist. mkd. T24S R6W S17 BT.
A Laurel 10" dia., bears S.21°E., 65 lks. dist. mkd. T24S R6W S20 BT.
A Fir 20" dia., bears S.69°W., 135 lks. dist. mkd. T24S R6W S19 BT.
A Fir 11" dia., bears N.54°W., 112 lks. dist. mkd. T24S R6W S18 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S.A. Bilow - March 26, 1959 - C.S. File 49/83-3

Found - 14" x 10" x 5" stone at corner with "F" chiseled on North slope.
Orig. 20" now 40" Fir S.69°W., 89.1 ft. shows scar, I do not open.
Orig. 14" now 36" Fir, previously opened, shows good scribed "T24S S17"
I check distances by measuring on slope to both BTs. Base of large Laurel stump that checks bearing and distance for orig. SE BT.
Set Brass cap alongside corner stone mkd:
County Surveyors Office
T 24 S R 6 W
S 18 | S 17
S 19 | S 20
1959
New BTs -3" Laurel bears N.51°E., 45.7 ft. scribed S17 CS BT
3" Laurel bears N.18°W., 35.5 ft. scribed S18 CS BT
4" Laurel bears S.17½°E., 66.4 ft. scribed S20 CSBT

BLM dependent resurvey by Joseph S. Gawron under Group #464 surveyed May/June 1962 (DCSO records Vol. 31 Page(s) 13121-22)

The Sec. cor. which is monumented with a sandstone 14x10x5 ins. firmly set 8" in the ground, mkd. "F" on the W. face; perpetuated by a County survey mark, an iron post 1½" dia., firmly set 24" in the ground, with 1959 brass cap
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of the original bearing trees
A Fir snag 36" dia., bears N.79°E., 77 lks. dist., mkd. T24S S17.
A burned Madrone stump bears S.21°E., 65 lks. dist.
A Fir snag 40" dia., bears S.69°W., 135 lks. dist., mkd. S19 T24S.
and trees mkd. by the County
A Madrone 4" dia., bears N.51°E., 69 lks. mkd. S17 CS BT
A Madrone 5" dia., bears S.17½°E., 100 lks. mkd. S20 CSBT
A Madrone 4" dia., bears N.18°W., 54 lks. mkd. S18 CS BT
and new bearing trees
A Madrone 6" dia., bears N.26°E., 138 lks. dist., mkd. T24S R6W S17 BT.
A Madrone 6" dia., bears S.54°E., 57 lks. dist., mkd. T24S R6W S20 BT.
A Madrone 6" dia., bears S.45°W., 78 lks. dist., mkd. T24S R6W S19 BT.
A Madrone 6" dia., bears N.60°W., 148 lks. dist., mkd. T24S R6W S18 BT.

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed June/July 2003, - (DCSO records Vol. 54 Page(s) 21120-1)

The cor. of secs. 17, 18, 19, and 20, monumented with a sandstone, 14x10x5", firmly set 8" in the ground, mkd. F on W face, with an iron post, 1½" dia., firmly set, projecting 12" above ground, plumbed over the original stone, with brass cap (properly) mkd.
from which the remains of original bearing trees
A roothole, bears S.69°W., 89.1 ft., with fir trunk, 25" dia., lying alongside, with no marks visible.
A decayed madrone stump, size indeterminate, bears S.21°E., 42.9 ft., with no marks visible.
and the remains of bearing trees mkd. by the Douglas County Surveyor's Office, in 1959, and reported by Gawron
A dead madrone, 16" dia., bears N.51°E., 45.5 ft., with no marks visible.
A dead madrone, 15" dia., bears S.17½°E., 66.0 ft., with a healed blaze.
A dead madrone, 11" dia., bears N.18°W., 35.6 ft., with no marks visible.
and the remains of a bearing tree mkd. by Gawron
A dead madrone, 7" dia., bears S.45°W., 51.5 ft., with no marks visible. (Record, S.47°W.)

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

- and new bearing trees
- A fir, 14" dia., bears N.22¾°E., 26.2 ft., mkd. T24S R6W S17 BT.
- A fir, 13" dia., bears S.7½°E., 14.4 ft., mkd. T24S R6W S20 BT.
- A fir, 7" dia., bears S.54¾°W., 14.2 ft., mkd. T24S R6W S19 BT.
- A fir, 10" dia., bears N.63½°W., 11.0 ft., mkd. T24S R6W S18 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center
This cor. is located at the cor. of woven wire fences extending North, South, East, and West.
The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade GPS receiver (Trimble GEO Explorer 3) observation, is as follows:
Latitude: 43°28'32.8"N. Longitude: 123°26'45.9"W.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2963, surveyed Jan/April 2020- (DCSO records Vol. 59 Page(s) 23980-1)

The cor. of secs. 17, 18, 19, and 20, reported by Moore and Browning in 2003; monumented with the original sandstone, 14x10x5", firmly set, projecting 6" above ground, with chisel mark F on W. face; with an iron post, 1¼" dia., firmly set, projecting 12" above ground, plumbed over the original stone, with a brass cap (properly) mkd.

- from which the remains of BTs reported by Moore & Browning
- A fir, 18" dia., bears N.22¾°E., 26.2 ft., with a healed blaze.
- A decayed madrone stump, 16" dia., bears N.51°E., 45.5 ft., no marks visible.
- A madrone snag, 15" dia., bears S.17½°E., 66.0 ft., with a healed blaze.
- A fir, 18" dia., bears S.7½°E., 14.4 ft., with a healed blaze.
- A fir snag, 8" dia., bears S.54¾°W., 14.2 ft., with a healed blaze.
- A broken, decayed fir stump size indeterminate, bears S.69°W., 89.1 ft., no marks visible. (Original)
- A fir, 12" dia., bears N.63½°W., 11.0 ft., with a healed blaze.

- and a new bearing tree
- A fir, 11" dia. bears S.79¼°W., 17.8 ft., mkd. T24S R6W S19 BT.

Continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

At the corner point
Removed the original stone and reset the iron post, 36" long,
1¼" dia., 24" in the ground. Add the marks BLM 2020 to the
cap. Bury the stone alongside the cor.