

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3183)

Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 18" dia., bears S.78°30'W., 11 lks. mkd. ¼ S BT.
A Fir 24" dia., bears N.75°30'E., 50 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - March 25, 1960 - C.S. File 49/83-30

Found - Orig. 24" now 30", down and partly rotted, Fir S.78°30'W., 7.3 ft. Find good scribing "¼"
Orig. 18" now 40" Fir N.75°30'E., shows good scar, I do not open.
Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
¼ S18|S17
1960
New BTs -6" R.Fir bears S.71°E., 6.0 ft. scribed ¼ S17 CSBT
8" R.Fir bears N.69°W., 45.8 ft. scribed ¼ S18 CSBT

Ken Hoffine - For: Lone Rock Timberland & Roseburg Resources - May 2014 - M168-11

Found - 1960 county cap 18" above ground.
20" D.Fir bears N.69¼°W., 45.1 ft (record N.69°W., 45.8 ft) healed face and tag
24" D.Fir bears S.73¼°E., 6.3 ft (record S.71°E., 6.0 ft) healed face and tag
22" D.Fir bears N.53¼°W., 19.4 ft unrecorded tree but has healed face and tag which reads S.56½°E., 32 lks (21.12 ft)
Corner lies on steep North facing slope approx. 30 ft North of small near vertical pitch.