

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3184)

Cut cross in sandstone bedrock for cor. to secs. 7, 8, 17 and 18, mkd. 8 on NE.; 17 on SE.; 18 on SW.; and 7 on NW. with 4 notches on the S. and 5 notches on the E, thus $\frac{7}{18}$ from which

- A Fir 18" dia., bears N.18°30'E., 65 lks. mkd. T24S R6W S8 BT.
- A Fir 15" dia., bears S.33°45'E., 101 lks. dist. mkd. T24S R6W S17 BT.
- A Fir 36" dia., bears S.58°W., 92 lks. dist., mkd. T24S R6W S18 BT.
- A Fir 20" dia., bears N.75°15'W., 65 lks. dist., mkd. T24S R6W S7 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Aug. 1959 - C.S. File 49/83-24

Found - Orig. 18" now 30" Fir snag, N.18°30'E., 42.9 ft., shows good scribing "B"
Orig. 15" now 32" Fir, S.33°45'E., 66.7 ft., shows good scar, I do not open.
Orig. NW BT, now snag.
Orig. SW BT, now stump.

Also find chiseled marks as recorded at corner on sandstone ledge. Corner is in approx. center of 50 ft. radius opening. I do not set brass cap.

- New BTs -30" Cedar bears S.4°W., 69.0 ft. scribed S18 T24S R6W CS BT.
- 18" forked Cedar S.61½°E., 61.6 ft. scribed S17 T24S R6W CS BT.
- 12" R.Fir bears N.36°W., 47.0 ft. scribed S7 T24S R6W CS BT.
- 7" Laurel bears N.10°E., 45.3 ft. scribed S8 T24S R6W CS BT.

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed June/July 2003, - (DCSO records Vol. 54 Page(s) 21121-2)

The cor. of secs. 7, 8, 17, and 18, monumented with an X chiseled into solid sandstone bedrock, and the marks 7, 8, 17, & 18 visible around it, from which the remains of orig. BTs. continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A decayed fir stump, size indeterminate, bears N.18½°E., 42.9 ft., with no marks visible.
 A sawed fir stump, 27 ins. diam., bears S.33¾°E., 63.1 ft., with a healed blaze. (Record, 66.7 ft.)
 A sawed fir stump, 27 ins. diam., bears S.65¾°W., 60.7 ft., with no marks visible. (Record, S.58°W.)
 and the remaining bearing trees mkd. by the Douglas County Surveyor's Office, in 1959
 A madrone, 11" dia., bears N.8¾°E., 45.2 ft., with a healed double blaze.
 A fir, 25" dia., bears N.37½°W., 47.1 ft., with a healed double blaze.
 At the corner point
 Set an alum. rod, 15 ins. long, ¾" dia., cemented 5" into a drill hole, 1" dia., centered over the X in the sandstone bedrock, with an alum. cap mkd.

T24S	R6W
S 7	S 8
S 18	S 17
2003	

This cor. is located in center of a clearing, 120 ft. diam., on a moderate W. slope.
 The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade GPS receiver (Trimble GEO Explorer 3) observation, is as follows:
 Latitude: 43°29'24.8"N. Longitude: 123°26'46.1"W.

Robert Ward - Ron Rice & Josh Reed, crew - June 2010 - C.S. File 65/69-24

 Found - BLM Aluminum Cap (properly marked) dated 2003 with the following Accessories;
 Decayed Fir Stump bears N.18½°E., 42.9' no marks visible.
 27" Fir Stump bears S.33¾°E, 63.1' healed face
 27" Fir Stump bears S.65¾°W, 60.7' no marks visible
 12" Madrone bears N.8¾°E., 45.2' healed double blaze
 25" Fir bears N.37½°W., 47.1' healed double blaze.
 16" Fir bears S.18¼°W., 89.9' healed face (unrecorded BLM)
 18" Fir Bears S11¾°E, 78.6' healed face (unrecorded BLM)

Fd. as per CS 65/29-24 by D Edwards, 7/2016 - C.S. 65/92-14