

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3191)

Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Cedar 42" dia., bears S.58°E., 77 lks. dist. mkd. ¼ S BT
A Fir 4" dia., bears N.59°30'W., 89 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - Sept. 2, 1970 - C.S. File 52/102-11

Found - 42" Cedar, now down, S.58°E., 50.8 ft. scribe visible "¼S".

No trace of NW BT, 4" Fir.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
¼ S6|S5
1970

New BTs -11" D.Fir S.67°E., 35.4 ft. mkd. ¼ S5 CS BT.
14" Maple N.45°W., 75.0 ft. mkd. ¼ S6 CS BT.

Mark Smalley - for: Roseburg Forest Products - Dec. 9, 1996 - C.S. 65/15-6B

Mon. Fd- 1970 DCSO I.P.B.C.

Bt's Fd- 11" D.Fir, S.67°E., 35.4' dead & down
16" Maple, N.45°W., 75' fair - healed face

New Accessories -

12" Fir, S.78°E., 18.6' scribed "¼ S BT"

8" Fir, S.80°W., 2.6' scribed "¼ S BT"

10" Fir, N.77°E., 21.1' scribed "¼ S BT"

Robert Ward - Ron Rice & Josh Reed, crew - June 2010 - C.S. File 65/69-37

Found - DCSO BC (properly marked)

16" Maple stump bears N.45°W., 75.0' (face scar)

15" D.Fir bears S.78°E., 18.6' (healed face)

12" D.Fir bears S.80°W., 2.6' (healed face)

15" D.Fir bears N.77°E., 21.1' (healed face)

New BT - 16" D.Fir bears N.45°W. 47.8' (scribed "¼ S6 BT")