

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 32; & 5, T25-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853  
(DCSO records, Volume 8 Page 3132)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia. bears N.4°W., 12 lks. dist.  
A Fir 12" dia. bears S.5°E., 16 lks. dist.

Volume 2 Page 265 - Date ? - By ?  
Visible-----  
Set Sandstone 5"x5"x18" for 1/4 corner on South side Sec. 32  
Alder 20" dia. bears S.50°20'W., 75 lks. dist.  
W.Oak 20" dia. bears N.65°45'E., 115 lks. dist.  
Gov't BTs were gone. Old rock was found set by previous  
Surveyor Co. Surveyor.

A. Boyer - Willis Ausland, January 1942 - C.S. File 36/18  
Volume 4 Pg 86  
-----  
24" Alder S.50°20'W., 49.5 ft. still standing but partly  
decayed. Found 5x5x8 rock. New trees set:  
8" Fir N.72°W., 37.7 ft.  
8" Forked Ash S.57°E., 35.3 ft.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; Mike Stone  
November 1962 - C.S. File 49/123-52  
-----  
Found - Rock called for in earlier renewals.  
14" W.Fir snag N.72°W. 37.7 ft. standing but rotten.  
Scribing visible "¼ BT".  
No trace of Boyer's SE tree.  
Rotten Alder snag S.50½°W., 49.5 ft. no markings  
found.  
Clump of Ash growing out of old stump hole,  
N.65 ¾°E., 76.0 ft. (Renewal calls for 20"  
W.Oak N.65 ¾°E., 75.9 ft.)  
No trace of original BTs found.  
Set brass cap alongside rock mkd:  
County Surveyors ¼ S32 T24S  
Office, 1962 S5 T25S R6W  
New BTs- 11" W.oak N.51°W., 45.7 ft. mkd. ¼ S32 CS BT.  
12" Ash S.50°W., 28.2 ft. mkd. ¼ S5 CS BT.  
Cor. lies in fence cor. fences South & West from corner.

Continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32; & 5, T25-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mark Smalley - For: Roseburg Forest Products - April 1998 -  
M 128-74

-----

Found - 1962 County brass cap on iron pipe & sandstone.  
16" W.Oak, N.51°W., 45.7', healed.  
12" Ash, S.50°W., 28.2', not tree, Ash clump.  
Scribed- 9" Ash, South 37.6', "¼ S BT"  
22" Fir, S.28°E., 105.7', "¼ S BT"