

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3185)

-----  
Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Fir 34" dia., bears N.69°E., 72 lks. dist. mkd. ¼ S BT.  
A Cedar 20" dia., bears S.35°E., 50 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Aug. 1959 - C.S. File 49/83-25

-----  
Found - Fir stump, now 46" dia., N.69°E., 47.5 ft. Chopped open scar enough to expose scribe "S". This was fine scribe, characteristic of Whipple.  
Cedar tree with center rotted out, S.35°E., 33 ft., no scribing found.

Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 6 W

¼  $\frac{S \ 8}{S \ 17}$   
1959

Blaze and scribe new trees:

10" R.Cedar N.49°E., 21.6 ft. mkd. ¼ S8 CS BT.  
7" Hemlock S.49°W., 17.3 ft. mkd. ¼ S17 CS BT.

Robert Ward - Ron Rice & Josh Reed, crew - June 2010 - C.S. File 65/69-23

-----  
Found - County Surveyors Office Brass Cap dated 1959 (properly marked) with the following Accessories:  
Decayed 46" Fir Stump Bears N.69°E., 47.5' no marks visible.

25" R.Cedar bears N.49°E., 21.6' healed face.  
7" Hemlock now blow down

New - 18" Hemlock bears S.65°E., 11.0' scribed "¼ S17 BT"  
10" Fir bears S.29°W., 16.9' scribed "¼ S17 BT"  
8" Fir Bears N.85°E., 22.7' scribed "¼ S8 BT"  
Compass Declination: 17½°E