

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2389)

Set ¼ sec. post, from which
A Fir 7" dia., bears N.3°W., 32 lks.
A Fir 9" dia., bears S.3°W., 31 lks.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3180-81)

The ¼ sec. cor.; post gone, reestablish same by setting a Fir post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S on N. face, from which
Stump or original bearing tree, bears S.3°W., 31 lks. dist.
No trace of other bearing tree to be seen excepting that there is some rotten wood lying around where it stood.
Marked new bearing trees as follows:
A Fir 60" dia., bears N.48°45'E., 56 lks. dist., mkd. ¼ S BT.
A Fir 20" dia., bears S.68°45'E., 57 lks. dist., mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12647)

The ¼ sec. cor., determined at record bearing and distance from the remains of the original bearing trees:
A Fir stump 56" dia., bears N.48°E., 59 lks. dist., mkd. ¼ S32 BT.
A Fir 30" dia., bears S.72°E., 59 lks. dist., mkd. ¼ S5.
At the corner point
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:
T23SR6W
¼ $\frac{S\ 32}{S\ 5}$
T24S
1957

from which
A Hemlock 10" dia., bears N.58°W., 11½ lks. dist., mkd. ¼ S32 BT.
A Fir 16" dia., bears S.61°W., 79½ lks. dist., mkd. ¼ S5 BT.

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T23-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Sept. 1, 1966 - C.S. 52/102-28

Found - GLO brass cap mkd. T23S R6W ¼ S32-5, T24-6W., 1957.
16" now 18" W. Fir stump, S.61°W., 52.8 ft. nearly
healed blazes, partial scribe marks visible.
Orig. NE BT is stump.
Orig. SE BT, turned out.
1957 NW BT, turned out.
New BTs -9" Hemlock S.40½°E., 30.8 ft. mkd. ¼ S5 CS BT.
10" D. Fir N.38°W., 86.5 ft. mkd. ¼ S32 CS BT.
Corner lies in old, logged-off unit.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Pages 19450-51)

The ¼ sec. cor. of secs. 5 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23S R6W
¼ $\frac{S32}{S5}$
T24S R6W
1957

from which the remains of bearing trees mkd. by Whipple
A sawed fir stump, 66" diam., bears N.48°E., 59 lks. dist with knife marks ¼S visible on open blaze facing S.
A root hole, bears S. 72° E., 59 lks. dist., alongside of which is lying a fir, 30 ins. diam., no marks visible on open blaze.
and a bearing tree mkd. by Gould, Gawron, and Eggen
A hemlock, 28 ins. diam., bears S. 61° W., 79½ lks. dist., with healed double blaze. (Record, fir.)
and the remains of bearing trees mkd. by Tracy, in 1966,
A hemlock, 18 ins. diam., bears S. 40½° E., 46½ lks. dist., with healed blaze.
A rootwad, bears N. 38° W., 131 lks. dist., alongside of which is lying a rotted fir log, 10 ins. diam., with fragmentary scribe marks visible on rotted blaze.
and a new bearing tree
A fir, 10 ins. diam., bears N. 41° W., 12 lks. dist., mkd. ¼ S32 BT

continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T23-6

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Robert Ward - Ron Rice & Josh Reed, crew - June 2010 - C.S.
File 65/69-25

Found - BLM Brass Cap (properly marked) dated 1957 with the following Accessories:
66" Fir Stump bears N.48°E., 38.9' healed face.
34" W.Fir bears S.61°W., 52.5' healed face (BLM reported as Hemlock)
20" Hemlock bears S.40½°E, 30.7' healed face.

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Mean Mustard & Galagher Canyon 1- Task A - Aug. 2023 - M185-5 A-D

Found - 3¼" GLO brass cap (properly mkd), 0.9' above ground with mound of stone from which:
A 13" Fir bears N.41°W., 7.7 ft with healed blaze and BT sign (1993)
A 17" Fir bears N.22°E., 8.7 ft with healed blaze and BT sign (no record)
A 19" snag bears S.42°E., 30.7 ft with healed blaze and BT sign (2010)
A 37" Hemlock bears S.60°W., 52.5 ft with healed blaze and BT sign (2010)
A roothole bears S.71°E., 40.6 ft with 24" trunk alongside with blaze (1891)
A 66" stump (4' high) bears N.48°E., 39.4 ft
(Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs)